



## Chain Sling G80 4-leg with Sling Hooks and Grab Hooks

### Product information

High quality 4-leg chain sling equipped with sling hooks and shortening hooks. Manufactured with high quality grade 80. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Safety factor:** 4:1

**Grade:** 8

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42071427W	6	2.36	0.5	13.91
42070063W	6	2.36	1.5	15.41
42071433W	6	2.36	1	15.51
42071436W	6	2.36	2.5	18.61
42071445W	6	2.36	3	21.91
42070073W	6	2.36	2	22.11
42071442W	6	2.36	3.5	23.51
42071449W	6	2.36	4	25.11

42071453W	6	2.36	5	31.71
42071457W	6	2.36	6	34.91
42071461W	8	4.25	0.5	17.334
42070175W	8	4.25	1	20.034
42070102W	8	4.25	1.5	22.734
42070103W	8	4.25	2	25.434
42070083W	8	4.25	2.5	28.134
42070113W	8	4.25	3	30.834
42070136W	8	4.25	3.5	33.534
42071474W	8	4.25	4	36.234
42071478W	8	4.25	5	41.634
42070087W	8	4.25	6	47.034
42071330W	10	6.7	0.5	23.4
42070126W	10	6.7	1	27.7
42071334W	10	6.7	1.5	32
42070089W	10	6.7	2	36.3
42070176W	10	6.7	2.5	40.6
42070092W	10	6.7	3	44.9
42070389W	10	6.7	3.5	49.2
42070218W	10	6.7	4	53.5
42070095W	10	6.7	5	62.1
42070414W	10	6.7	6	70.7
42071356W	13	11.2	0.5	41.56

42071363W	13	11.2	1	48.56
42071360W	13	11.2	1.5	55.56
42070356W	13	11.2	2	62.56
42071367W	13	11.2	2.5	69.56
42070407W	13	11.2	3	76.56
42071373W	13	11.2	3.5	83.56
42070061W	13	11.2	4	90.56
42071381W	13	11.2	5	104.56
42071385W	13	11.2	6	118.56
42071397W	16	17	1	78.15
42071393W	16	17	1.5	89.15
42071404W	16	17	2	100.15
42071401W	16	17	2.5	111.15
42071412W	16	17	3	122.15
42071408W	16	17	3.5	133.15
42071416W	16	17	4	144.15
42071420W	16	17	5	166.15
42071424W	16	17	6	188.15

## Blueprint

