

## Chain Sling G80 4-leg with Sling Hooks



### Product information

High quality 4-leg chain sling equipped with sling hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Safety factor:** 4:1

**Grade:** 8

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070062W	6	2.36	0.5	11.65
42071432W	6	2.36	1	13.25
42070138W	6	2.36	1.5	14.85
42071438W	6	2.36	2	16.45
42071435W	6	2.36	2.5	18.05
42071444W	6	2.36	3	19.65
42071441W	6	2.36	3.5	21.25
42071448W	6	2.36	4	22.85

42071452W	6	2.36	5	26.05
42071456W	6	2.36	6	29.25
42071460W	8	4.25	0.5	19.754
42070075W	8	4.25	1	22.454
42070077W	8	4.25	1.5	25.154
42070146W	8	4.25	2	27.854
42070082W	8	4.25	2.5	30.554
42070085W	8	4.25	3	33.254
42070195W	8	4.25	3.5	35.954
42071473W	8	4.25	4	38.654
42071477W	8	4.25	5	44.054
42071481W	8	4.25	6	49.454
42071329W	10	6.7	0.5	20.8
42070202W	10	6.7	1	25.1
42071333W	10	6.7	1.5	29.4
42070088W	10	6.7	2	33.7
42070201W	10	6.7	2.5	38
42070416W	10	6.7	3	42.3
42071342W	10	6.7	3.5	46.6
42071346W	10	6.7	4	50.9
42071349W	10	6.7	5	59.5
42071352W	10	6.7	6	68.1
42071355W	13	11.2	0.5	36

42070368W	13	11.2	1	43
42071359W	13	11.2	1.5	50
42070059W	13	11.2	2	57
42071366W	13	11.2	2.5	64
42070277W	13	11.2	3	71
42071372W	13	11.2	3.5	78
42071377W	13	11.2	4	85
42071380W	13	11.2	5	99
42071384W	13	11.2	6	113
42071396W	16	17	1	69.35
42071392W	16	17	1.5	80.35
42070199W	16	17	2	91.35
42071400W	16	17	2.5	102.35
42071411W	16	17	3	113.35
42071407W	16	17	3.5	124.35
42071415W	16	17	4	135.35
42071419W	16	17	5	157.35
42071423W	16	17	6	179.35

## Blueprint

