

## Chain Sling G80 4-leg with Safety Hooks and Grab Hooks

### Product information



High quality 4-leg chain sling equipped with self-locking hooks with shortening hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight. [... Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow

**Standard:** EN 818-4

**Safety factor:** 4:1

**Grade:** 8

## Chain Sling G80 4-leg with Safety Hooks and Grab Hooks

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070780W	6	2.36	0.5	12.93
42070783W	6	2.36	1	14.53
42070781W	6	2.36	1.5	16.13
42070787W	6	2.36	2	17.73
42070785W	6	2.36	2.5	19.33
42070791W	6	2.36	3	20.93
42070789W	6	2.36	3.5	22.53
42070793W	6	2.36	4	24.13
42070795W	6	2.36	5	27.33
42070797W	6	2.36	6	30.53
42070799W	8	4.25	0.5	20.314
42070803W	8	4.25	1	23.014
42070801W	8	4.25	1.5	25.714
42070183W	8	4.25	2	28.414
42070306W	8	4.25	2.5	31.114
42070084W	8	4.25	3	33.814
42070805W	8	4.25	3.5	36.514
42070111W	8	4.25	4	39.214
42070808W	8	4.25	5	44.614
42070171W	8	4.25	6	50.014
42070731W	10	6.7	0.5	25.6
42070735W	10	6.7	1	29.9

## Chain Sling G80 4-leg with Safety Hooks and Grab Hooks

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070733W	10	6.7	1.5	34.2
42070154W	10	6.7	2	38.5
42070114W	10	6.7	2.5	42.8
42070090W	10	6.7	3	47.1
42070239W	10	6.7	3.5	51.4
42070094W	10	6.7	4	55.7
42070740W	10	6.7	5	64.3
42070742W	10	6.7	6	72.9
42070744W	13	11.2	0.5	43.01
42070748W	13	11.2	1	50.01
42070746W	13	11.2	1.5	57.01
42070752W	13	11.2	2	64.01
42070750W	13	11.2	2.5	71.01
42070756W	13	11.2	3	78.01
42070754W	13	11.2	3.5	85.01
42070359W	13	11.2	4	92.01
42070213W	13	11.2	5	106.01
42070759W	13	11.2	6	120.01
42070765W	16	17	1	86.95
42070763W	16	17	1.5	97.95
42070769W	16	17	2	108.95
42070767W	16	17	2.5	119.95
42070247W	16	17	3	130.95
42070771W	16	17	3.5	141.95
42070774W	16	17	4	152.95
42070776W	16	17	5	174.95
42070778W	16	17	6	196.95