

Chain Sling G80 4-leg with Safety Hooks

Product information



High quality 4-leg chain sling equipped with self-locking hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Safety factor: 4:1

Grade: 8

Chain Sling G80 4-leg with Safety Hooks

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070779W	6	2.36	0.5	15.77
42070782W	6	2.36	1	17.37
42070207W	6	2.36	1.5	18.97
42070786W	6	2.36	2	20.57
42070784W	6	2.36	2.5	22.17
42070790W	6	2.36	3	23.77
42070788W	6	2.36	3.5	25.37
42070792W	6	2.36	4	26.97
42070794W	6	2.36	5	30.17
42070796W	6	2.36	6	33.37
42070798W	8	4.25	0.5	21.034
42070802W	8	4.25	1	23.734
42070800W	8	4.25	1.5	26.434
42070078W	8	4.25	2	29.134
42070166W	8	4.25	2.5	31.834
42070806W	8	4.25	3	34.534
42070804W	8	4.25	3.5	37.234
42070167W	8	4.25	4	39.934
42070807W	8	4.25	5	45.334
42070809W	8	4.25	6	50.734
42070730W	10	6.7	0.5	23
42070734W	10	6.7	1	27.3

Chain Sling G80 4-leg with Safety Hooks

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070732W	10	6.7	1.5	31.6
42070327W	10	6.7	2	35.9
42070736W	10	6.7	2.5	40.2
42070393W	10	6.7	3	44.5
42070737W	10	6.7	3.5	48.8
42070738W	10	6.7	4	53.1
42070739W	10	6.7	5	61.7
42070741W	10	6.7	6	70.3
42070743W	13	11.2	0.5	42.55
42070747W	13	11.2	1	49.55
42070745W	13	11.2	1.5	56.55
42070751W	13	11.2	2	63.55
42070749W	13	11.2	2.5	70.55
42070755W	13	11.2	3	77.55
42070753W	13	11.2	3.5	84.55
42070268W	13	11.2	4	91.55
42070757W	13	11.2	5	105.55
42070758W	13	11.2	6	119.55
42070764W	16	17	1	67.95
42070762W	16	17	1.5	78.95
42070768W	16	17	2	93.35
42070766W	16	17	2.5	104.35
42070772W	16	17	3	115.35
42070770W	16	17	3.5	126.35
42070773W	16	17	4	137.35
42070775W	16	17	5	159.35
42070777W	16	17	6	181.35