

Chain Sling G80 3-leg with Sling Hooks and Grab hooks



Product information

High quality 3-leg chain sling equipped with sling hooks and shortening hooks. Manufactured with high quality grade 80. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42071256W	6	2.36	0.5	12.97
42071262W	6	2.36	1	14.17
42071259W	6	2.36	1.5	15.37
42071270W	6	2.36	2	16.57
42071266W	6	2.36	2.5	17.77
42070450W	6	2.36	3	18.97
42071274W	6	2.36	3.5	20.17
42071281W	6	2.36	4	23.07

42071285W	6	2.36	5	25.47
42071289W	6	2.36	6	29.57
42071293W	8	4.25	0.5	14.088
42071300W	8	4.25	1	16.113
42071296W	8	4.25	1.5	18.138
42071307W	8	4.25	2	20.163
42070112W	8	4.25	2.5	22.188
42070055W	8	4.25	3	24.213
42071311W	8	4.25	3.5	26.238
42071318W	8	4.25	4	28.263
42071322W	8	4.25	5	34.013
42071326W	8	4.25	6	38.063
42071140W	10	6.7	0.5	20.425
42071148W	10	6.7	1	23.65
42071144W	10	6.7	1.5	26.875
42070370W	10	6.7	2	30.1
42070056W	10	6.7	2.5	33.325
42070216W	10	6.7	3	36.55
42071158W	10	6.7	3.5	39.775
42071165W	10	6.7	4	43
42071169W	10	6.7	5	49.45
42071173W	10	6.7	6	55.9
42071177W	13	11.2	0.5	35.97

42071185W	13	11.2	1	41.22
42071181W	13	11.2	1.5	46.47
42071193W	13	11.2	2	51.72
42071189W	13	11.2	2.5	56.97
42070098W	13	11.2	3	62.22
42071197W	13	11.2	3.5	67.47
42071204W	13	11.2	4	72.72
42071208W	13	11.2	5	83.22
42071212W	13	11.2	6	93.72
42071224W	16	17	1	65.9
42071220W	16	17	1.5	74.15
42071232W	16	17	2	82.4
42071228W	16	17	2.5	90.65
42071240W	16	17	3	98.9
42071236W	16	17	3.5	107.15
42071244W	16	17	4	115.4
42071248W	16	17	5	131.9
42071252W	16	17	6	148.4

Blueprint

