

Chain Sling G80 3-leg with Safety Hooks and Grab Hooks

Product information



High quality 3-leg chain sling equipped with self-locking hooks with shortening hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight. [... Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Safety factor: 4:1

Grade: 8

Chain Sling G80 3-leg with Safety Hooks and Grab Hooks

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070691W	6	2.36	0.5	16.91
42070699W	6	2.36	2	17.11
42070695W	6	2.36	1	18.11
42070697W	6	2.36	2.5	18.31
42070693W	6	2.36	1.5	19.31
42070703W	6	2.36	3	22.91
42070701W	6	2.36	3.5	24.11
42070707W	6	2.36	5	24.31
42070705W	6	2.36	4	25.31
42070709W	6	2.36	6	28.41
42070711W	8	4.25	0.5	18.448
42070715W	8	4.25	1	20.473
42070713W	8	4.25	1.5	22.498
42070719W	8	4.25	2	24.523
42070717W	8	4.25	2.5	26.548
42070723W	8	4.25	3	28.573
42070721W	8	4.25	3.5	30.598
42070725W	8	4.25	4	32.623
42070727W	8	4.25	5	36.673
42070729W	8	4.25	6	40.723
42070631W	10	6.7	0.5	22.075
42070635W	10	6.7	1	25.3

Chain Sling G80 3-leg with Safety Hooks and Grab Hooks

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070633W	10	6.7	1.5	28.525
42070639W	10	6.7	2	31.75
42070637W	10	6.7	2.5	34.975
42070643W	10	6.7	3	38.2
42070641W	10	6.7	3.5	41.425
42070645W	10	6.7	4	44.65
42070647W	10	6.7	5	51.1
42070649W	10	6.7	6	57.55
42070651W	13	11.2	0.5	36.42
42070655W	13	11.2	1	41.67
42070653W	13	11.2	1.5	46.92
42070659W	13	11.2	2	52.17
42070657W	13	11.2	2.5	57.42
42070663W	13	11.2	3	62.67
42070661W	13	11.2	3.5	67.92
42070665W	13	11.2	4	73.17
42070667W	13	11.2	5	83.67
42070669W	13	11.2	6	94.17
42070675W	16	17	1	69.1
42070673W	16	17	1.5	77.35
42070679W	16	17	2	85.6
42070677W	16	17	2.5	93.85
42070683W	16	17	3	102.1
42070681W	16	17	3.5	110.35
42070685W	16	17	4	118.6
42070687W	16	17	5	135.1
42070689W	16	17	6	151.6