Chain Sling G80 2-leg with Sling Hooks and Grab Hooks

Product information



High quality 2-leg chain sling equipped with sling hooks and shortening hooks. Manufactured with high quality grade 80. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40°C up to +200°C / 400°C = WLL 75%
Finish: Painted, black / yellow
Standard: EN 818-4

Safety factor: 4:1
Grade: 8

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Chain Sling G80 2-leg with Sling Hooks and Grab Hooks

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42071082W	6	1.6	0.5	11.17
42070025W	6	1.6	1	11.97
42070100W	6	1.6	1.5	12.77
42070028W	6	1.6	2	13.57
42070026W	6	1.6	2.5	14.37
42071097W	6	1.6	3	15.17
42071093W	6	1.6	3.5	15.97
42070281W	6	1.6	4	16.77
42071103W	6	1.6	5	18.37
42071107W	6	1.6	6	19.97
42071111W	8	2.8	0.5	11.142
42070314W	8	2.8	1	12.492
42070210W	8	2.8	1.5	13.842
42070115W	8	2.8	2	15.192
42070131W	8	2.8	2.5	16.542
42070037W	8	2.8	3	17.892
42071122W	8	2.8	3.5	19.242
42070038W	8	2.8	4	20.592
42071132W	8	2.8	5	23.292
42071136W	8	2.8	6	25.992
42070988W	10	4.25	0.5	15.55
42070145W	10	4.25	1	17.7

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Sling G80 2-leg with Sling Hooks and Grab Hooks

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070365W	10	4.25	1.5	19.85
42070042W	10	4.25	2	22
42070045W	10	4.25	2.5	24.15
42070047W	10	4.25	3	26.3
42070150W	10	4.25	3.5	28.45
42070196W	10	4.25	4	30.6
42070181W	10	4.25	5	34.9
42071010W	10	4.25	6	39.2
42071014W	13	7.5	0.5	26.68
42070390W	13	7.5	1	30.18
42070406W	13	7.5	1.5	33.68
42070282W	13	7.5	2	37.18
42071023W	13	7.5	2.5	40.68
42070214W	13	7.5	3	44.18
42071029W	13	7.5	3.5	47.68
42070200W	13	7.5	4	51.18
42070158W	13	7.5	5	58.18
42071041W	13	7.5	6	65.18
42071053W	16	11.2	1	47.55
42071049W	16	11.2	1.5	53.05
42071060W	16	11.2	2	58.55
42071057W	16	11.2	2.5	64.05
42070029W	16	11.2	3	69.55
42071064W	16	11.2	3.5	75.05
42071071W	16	11.2	4	80.55
42071075W	16	11.2	5	91.55
42071079W	16	11.2	6	102.55

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved