Lifting Solutions Group
Axel Johnson International

Chain Sling G80 2-leg with Sling Hooks

Product information



High quality 2-leg chain sling equipped with sling hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40°C up to +200°C / 400°C = WLL 75%
Finish: Painted, black / yellow
Standard: EN 818-4

Safety factor: 4:1
Grade: 8

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Chain Sling G80 2-leg with Sling Hooks

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070185W	6	1.6	0.5	10.89
42070024W	6	1.6	1	11.69
42070143W	6	1.6	1.5	12.49
42071096W	6	1.6	3	13.19
42070027W	6	1.6	2	13.29
42070178W	6	1.6	4	14.79
42071092W	6	1.6	3.5	15.69
42071087W	6	1.6	2.5	17.49
42071106W	6	1.6	6	19.69
42071102W	6	1.6	5	21.49
42071110W	8	2.8	0.5	12.352
42070127W	8	2.8	1	13.702
42070031W	8	2.8	1.5	15.052
42070110W	8	2.8	2	16.402
42071118W	8	2.8	2.5	17.752
42071125W	8	2.8	3	19.102
42071121W	8	2.8	3.5	20.452
42071128W	8	2.8	4	21.802
42071131W	8	2.8	5	24.502
42071135W	8	2.8	6	27.202
42070987W	10	4.25	0.5	14.25
42070039W	10	4.25	1	16.4

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Chain Sling G80 2-leg with Sling Hooks

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070188W	10	4.25	1.5	18.55
42070041W	10	4.25	2	20.7
42070995W	10	4.25	2.5	22.85
42070439W	10	4.25	3	25
42070999W	10	4.25	3.5	27.15
42070050W	10	4.25	4	29.3
42071006W	10	4.25	5	33.6
42071009W	10	4.25	6	37.9
42071013W	13	7.5	0.5	21.35
42070121W	13	7.5	1	24.85
42071017W	13	7.5	1.5	28.35
42070378W	13	7.5	2	31.85
42071022W	13	7.5	2.5	35.35
42071032W	13	7.5	3	38.85
42071028W	13	7.5	3.5	42.35
42071035W	13	7.5	4	45.85
42070053W	13	7.5	5	52.85
42071040W	13	7.5	6	59.85
42071052W	16	11.2	1	43.15
42071048W	16	11.2	1.5	48.65
42070165W	16	11.2	2	54.15
42071056W	16	11.2	2.5	59.65
42071067W	16	11.2	3	65.15
42071063W	16	11.2	3.5	70.65
42071070W	16	11.2	4	76.15
42071074W	16	11.2	5	87.15
42071078W	16	11.2	6	98.15

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved