Lifting Solutions Group
Axel Johnson International

Chain Sling G80 1-leg with Sling Hook

Product information



High quality 1-leg chain sling equipped with sling hook. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

... *Read more*

Material: Steel
Marking: According to standard, CE-mark
Temperature range: -40°C up to +200°C / 400°C = WLL 75%
Finish: Painted, black / yellow
Standard: EN 818-4

Safety factor: 4:1
Grade: 8

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Chain Sling G80 1-leg with Sling Hook

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070191W	6	1.12	0.5	13.49
42070149W	6	1.12	1	13.89
42070927W	6	1.12	1.5	14.29
42070125W	6	1.12	2	14.69
42070931W	6	1.12	2.5	15.09
42070938W	6	1.12	3	15.49
42070935W	6	1.12	3.5	15.89
42070942W	6	1.12	4	16.29
42070946W	6	1.12	5	17.09
42070950W	6	1.12	6	17.89
42070174W	8	2	0.5	10.781
42070119W	8	2	1	11.456
42070957W	8	2	1.5	12.131
42070224W	8	2	2	12.806
42070964W	8	2	2.5	13.481
42070011W	8	2	3	14.156
42070190W	8	2	3.5	14.831
42070975W	8	2	4	15.506
42070979W	8	2	5	16.856
42070983W	8	2	6	18.206
42070812W	10	3.15	0.5	18.875
42070162W	10	3.15	1	19.95

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Chain Sling G80 1-leg with Sling Hook

Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070395W	10	3.15	1.5	21.025
42070163W	10	3.15	2	22.1
42070822W	10	3.15	2.5	23.175
42070832W	10	3.15	3	24.25
42070828W	10	3.15	3.5	25.325
42070836W	10	3.15	4	26.4
42070839W	10	3.15	5	28.55
42070843W	10	3.15	6	30.7
42070847W	13	5.3	0.5	16.35
42070854W	13	5.3	1	18.1
42070279W	13	5.3	1.5	19.85
42070861W	13	5.3	2	21.6
42070858W	13	5.3	2.5	23.35
42070869W	13	5.3	3	25.1
42070865W	13	5.3	3.5	26.85
42070872W	13	5.3	4	28.6
42070876W	13	5.3	5	32.1
42070880W	13	5.3	6	35.6
42070892W	16	8	1	28.1
42070888W	16	8	1.5	30.85
42070900W	16	8	2	33.6
42070896W	16	8	2.5	36.35
42070908W	16	8	3	39.1
42070904W	16	8	3.5	41.85
42070912W	16	8	4	44.6
42070916W	16	8	5	50.1
42070920W	16	8	6	55.6

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved