

## Chain Sling G80 1-leg with Safety Hook

### Product information



High quality 1-leg chain sling equipped with self-locking hook. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

... [Read more](#)

**Material:** Steel

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +200°C / 400°C = WLL 75%

**Finish:** Painted, black / yellow


**Standard:** EN 818-4

**Safety factor:** 4:1

**Grade:** 8

## Chain Sling G80 1-leg with Safety Hook

### Blueprint



### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070515W	6	1.12	0.5	10.27
42070197W	6	1.12	1	10.67
42070517W	6	1.12	1.5	11.07
42070141W	6	1.12	2	11.47
42070520W	6	1.12	2.5	11.87
42070524W	6	1.12	3	12.27
42070522W	6	1.12	3.5	12.67
42070526W	6	1.12	4	13.07
42070528W	6	1.12	5	13.87
42070530W	6	1.12	6	14.67
42070532W	8	2	0.5	12.801
42070198W	8	2	1	13.476
42070534W	8	2	1.5	14.151
42070539W	8	2	2	14.826
42070537W	8	2	2.5	15.501
42070543W	8	2	3	16.176
42070541W	8	2	3.5	16.851
42070544W	8	2	4	17.526
42070546W	8	2	5	18.876
42070548W	8	2	6	20.226
42070460W	10	3.15	0.5	19.425
42070164W	10	3.15	1	20.5

## Chain Sling G80 1-leg with Safety Hook

### Technical data

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070177W	10	3.15	1.5	21.575
42070466W	10	3.15	2	22.65
42070464W	10	3.15	2.5	23.725
42070470W	10	3.15	3	24.8
42070468W	10	3.15	3.5	25.875
42070472W	10	3.15	4	26.95
42070476W	10	3.15	6	28.7
42070474W	10	3.15	5	29.1
42070478W	13	5.3	0.5	17.35
42070482W	13	5.3	1	19.1
42070480W	13	5.3	1.5	20.85
42070318W	13	5.3	2	22.6
42070484W	13	5.3	2.5	24.35
42070489W	13	5.3	3	26.1
42070487W	13	5.3	3.5	27.85
42070491W	13	5.3	4	29.6
42070493W	13	5.3	5	33.1
42070495W	13	5.3	6	36.6
42070501W	16	8	1	33.7
42070499W	16	8	1.5	36.45
42070303W	16	8	2	39.2
42070503W	16	8	2.5	41.95
42070508W	16	8	3	44.7
42070511W	16	8	5	45.5
42070506W	16	8	3.5	47.45
42070510W	16	8	4	50.2
42070513W	16	8	6	51