Lifting Solutions Group
Axel Johnson International

Foundry Hook GHK/S Grade 10 - Clevis

Product information



Foundry Hooks are hooks with a bigger opening without safety latch often used in foundries.

... *Read more*

Material: Alloy steel.
Marking: According to standard, CE-mark
Temperature range: -40°C up to 380°C
Finish: Violet powder coated.
Standard: EN 818-4
Note: Always verify if hooks without safety latch are allowed for your application.
Warning: Not to be heat-treated.

Safety factor: 4:1
Grade: 10

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Foundry Hook GHK/S Grade 10 - Clevis

Blueprint



Technical data

Part code	Code	WLL ton	EWL mm	For chain Ø mm	a mm	b mm	d mm	e mm	g mm	h mm	Weight kg
402300250330	GHK/S-8-10	2.5	120	8	25	118	10	120	64	29	1.04
402300400330	GHK/S-10-10	4	140	10	32	143	12.5	140	76	35	1.74
402300670330	GHK/S-13-10	6.7	170	13	40	170	16	170	89	42	3.38

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved