Lifting Solutions Group
Axel Johnson International

Safety Hook HSB/S

Product information



Safety hook with Eye.

... *Read more*

Material: Alloy steel
Marking: According to standard, code and grade
Finish: Violet powder coated.
Standard: EN 1677-3 (+ 25% WLL)
Warning: Not to be heat-treated.

Safety factor: 4:1
Grade: 10


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Safety Hook HSB/S

Blueprint



Technical data

Part code	Code	WLL ton	EWL mm	a mm	b mm	d1 mm	d2 mm	e mm	g mm	h mm	S max mm	Weight kg
402300140400	HSB/S-6-10	1.4	110	17	71	21	11	110	28	20	1	0.52
402300250400	HSB/S-7/8-10	2.5	136	20	88	25	12	136	34	26	1	0.92
402300400400	HSB/S-10-10	4	169	29	107	35	17	169	45	30	1	1.57
402300670400	HSB/S-13-10	6.7	205	35	138	40	20	205	52	40	1.5	3.19
402301000400	HSB/S-16-10	10	251	41	168	50	27	251	60	50	2	6.24
402301600400	HSB/S-19/20-10	16	290	50	194	60	30	290	70	62	2	9.75
402301900400	HSB/S-22-10	19	322	52	211	70	32	322	81	65	2	11.45

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved