



Lifting Clamp STSU

Product information



General: For lifting and transporting of steel plates from all positions (horizontal, vertical and sidelong), articulated lifting shackle. The TSU /STSU/TSU-R lifting clamps are equipped with a safety mechanism, ensuring the clamp does not slip when lifting force is applied and when load is being lowered. The clamp is locked in closed as well as in open position.

Marking: Working load limit, jaw capacity and CE-marking.

Finish: Yellow painted.

Note: Min. load is 10% of WLL.

Safety factor: 5:1

Part Code	Code	WLL ton	Jaw width mm	S mm	T mm	U mm	V mm	W mm	X mm	Y mm	Weight kg
44010157B	6 STSU	6	40-90	114	78	523	275	70	78	32	24
44010032B	7.5 STSU	7.5	50-100	111	78	560	312	70	86	32	30
44010156B	9 STSU	9	50-100	111	78	560	312	70	86	32	31
44010151B	12 STSU	12	50-100	152	85	644	344	100	94	48	45
44010152B	15 STSU	15	80-150	224	85	808	450	136	106	48	78
44010153B	20 STSU	20	80-150	249	100	940	640	153	140	71	171
44010154B	25 STSU	25	80-150	249	100	940	640	153	140	71	171
44010155B	30 STSU	30	80-150	249	100	946	645	156	142	71	176.5

Blueprint

