

Lever Hoist KITO LX Series

Product information

The KITO LX Series is a range of small lever hoists that is suitable for operations in limited space. The lever hoist has a freewheel safeguard and the bottom hook is riveted in four places. Its solid aluminium housing enables a low weight of the hoist. The load can be lifted or lowered in 2 mm steps due to its smooth gear mechanism.

Material: High impact aluminium housing, nickel-plated load chain in grade 10.

Marking: CE-marked, Type plate with WLL, CE-marking and serial number.

Finish: Surface treated aluminium.

Safety factor: 4:1.

| Part Code | Code | WLL ton | Lifting height m | Hand pull to lift full load daN | Load chain Ø mm | Chain falls | A mm | B mm | C mm | D mm | e mm | g mm | t mm | s mm | Weight kg |
|-----------|-------|------------|---------------------|------------------------------------|--------------------|-------------|---------|---------|---------|---------|---------|---------|---------|---------|--------------|
| 43040040B | LX003 | 0.25 | 1.5 | 20 | 3,2 x 9,0 | 1 | 90,5 | 73,5 | 205 | 150 | 62 | 21,0 | 11 | 32 | 1.7 |
| 43040041B | - | 0.25 | 3 | 20 | 3,2 x 9,0 | 1 | - | - | - | - | - | - | - | - | 2 |
| 43040043B | LX005 | 0.5 | 1.5 | 31 | 4,3 x 12,0 | 1 | 102,0 | 93,0 | 246 | 180 | 68 | 24,5 | 12 | 35,5 | 2.7 |
| 43040044B | - | 0.5 | 3 | 31 | 4,3 x 12,0 | 1 | - | - | - | - | - | - | - | - | 3.3 |

Blueprint

