

## Stainless Eye Terminal

### Product information



Eye terminals for pressing or swaging onto stainless steel wire rope. They are mainly used as an attachment to rigging screws or forks.

**Material:** Stainless steel AISI 316.

**Marking:** logo, wire size and swage depth.

**Temperature range:** -50°C to +100°C and briefly up to +200°C

**Finish:** High polished.

| Part code   | Rope Ø range mm | MBL ton | A, | B, | D1 mm | D2 mm | L1 mm | L2 mm | Weight kg/100pc |
|-------------|-----------------|---------|----|----|-------|-------|-------|-------|-----------------|
| 1207190002  | 2               | 1.2     | 3  | 12 | 5,5   | 5,5   | 41    | 24    | 0.9             |
| 1207190025  | 2.5             | 1       | 3  | 12 | 5,5   | 5,5   | 44    | 27    | 0.8             |
| 1207190003  | 3               | 1.3     | 4  | 14 | 6,35  | 6,5   | 60    | 38    | 1.3             |
| 1207190004  | 4               | 1.7     | 5  | 17 | 7,5   | 8,5   | 67    | 45    | 2.3             |
| 1207190005  | 5               | 2.4     | 6  | 21 | 9,0   | 10,5  | 79    | 51    | 3.9             |
| 1207190006  | 6               | 5.5     | 8  | 25 | 12,58 | 13,0  | 94    | 64    | 8.7             |
| 1207190006X | 6               | 5.5     | 10 | 28 | 12,58 | 13,2  | 105   | 64    | 13.2            |
| 1207190007  | 7               | 6.8     | 9  | 27 | 14,2  | 13,0  | 104   | 70    | 11.5            |

|             |    |      |    |    |      |      |     |     |       |
|-------------|----|------|----|----|------|------|-----|-----|-------|
| 1207190007X | 7  | 6.8  | 10 | 28 | 14,2 | 13,2 | 110 | 70  | 13.5  |
| 1207190008  | 8  | 8    | 10 | 30 | 16,0 | 14,5 | 124 | 83  | 17    |
| 1207190008X | 8  | 8    | 12 | 36 | 16,0 | 16,5 | 141 | 83  | 23.5  |
| 1207190010  | 10 | 9.7  | 11 | 35 | 17,8 | 16,3 | 137 | 89  | 25    |
| 1207190010X | 10 | 9.7  | 16 | 40 | 17,8 | 19,5 | 165 | 100 | 38    |
| 1207190012X | 12 | 14.2 | 15 | 42 | 21,4 | 19,3 | 178 | 120 | 41    |
| 1207190012  | 12 | 11.4 | 15 | 40 | 20,0 | 19,3 | 156 | 105 | 41.5  |
| 1207190014  | 14 | 15.9 | 18 | 47 | 25,0 | 23,0 | 206 | 140 | 75.6  |
| 1207190016  | 16 | 19   | 20 | 53 | 28,0 | 26   | 232 | 160 | 102   |
| 1207190016  | 19 | 31   | 25 | 65 | 34,5 | 28,5 | 302 | 200 | 209   |
| 1207190020  | 20 | 31   | 25 | 65 | 34,5 | 28,5 | 302 | 200 | 199.8 |
| 1207190022  | 22 | 42   | 30 | 70 | 40,4 | 33,0 | 348 | 230 | 314   |
| 1207190026  | 26 | 53   | 30 | 77 | 46,0 | 36,0 | 400 | 280 | 425   |
| 1207190028  | 28 | 64   | 35 | 84 | 50   | 40,5 | 445 | 300 | 602   |

# Blueprint

