

## Roundslings FORANKRA R1 Side Seam

### Product information



High-quality roundslings made in accordance with PN-EN 1492-2, a Polish manufacturer who uses only top-grade materials from Europe for their production.

Characteristics:

- Markings: label with abbreviated instructions. Number of black stripes along the sling informs about the lifting capacity in tons.
- The highest versatility of use among slings.
- Excellent ratio of dead weight to lifting load.
- Can be used for lifting materials sensitive to damage, such as bundles of copper pipes, aluminum sections, etc.
- High resistance to moisture and typical contaminants, such as grease and oil.

**Material:** 100% PES, single sleeve, high quality polyester yarn.

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +100°C

**Standard:** EN 1492-2

**Note:** Colour Coded

Part code	WLL ton
41080022F	40
41080023F	40
41080024F	40
41080025F	40
41080026F	40
41080027F	40

41080028F	40
41080029F	40
41080030F	50
41080031F	50
41080032F	50
41080033F	50
41080034F	50
41080035F	50
41080036F	50
41080037F	50
41080038F	60
41080039F	60
41080040F	60
41080041F	60
41080042F	60
41080043F	60
41080044F	60
41080045F	60
41080046F	70
41080047F	70
41080048F	70
41080049F	70
41080050F	70

41080051F	70
41080052F	70
41080053F	70
41080054F	80
41080055F	80
41080056F	80
41080057F	80
41080058F	80
41080059F	80
41080060F	80
41080061F	80