Lifting Solutions Group
Axel Johnson International

Wire Rope Grip Powertex PWRG

Product information



Wire rope grip type Powertex is approved for lifting only if assembly is carried out according to the instruction manual.

The wire rope grips are designed for use with six-stranded right-hand lay ropes in 6x19 (M) and 6x36 classes and right-hand ordinary lay wire rope in 8x19 class up to 1960 N/mm², with fibre core and a steel core.

Correctly mounted the assembly will withstand 80% of the rope's minimum breaking load (MBL).

- Safe - The grips are designed to assure high friction between wire rope and grip
- PWRG is symmetrical and can be turned as preferred
- Quick and easy to use
- Quick mounting thanks to the recessed bolt head seats that hold the bolt while tightening the nuts
- Low maintenance thanks to galvanization of grips and Dacrotized bolt and nuts
- Tested according to EN 13411-5

... *Read more*

Material: PWRG-4 and -6 are drop forged. PWRG-8, -10, -12, -16, -20, -25, -35 are casted
Marking: Powertex (PX, PTEX), size and batch
Finish: Hot dip galvanized (HDG)
Warning: Not to be used with compacted, hammered or plastic coated steel wire ropes. It is not recommended to use plastic covered ropes for lifting purposes with wire rope grips.


Certex Polska
info@certex.pl
+48 91 817 28 49

© October 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Wire Rope Grip Powertex PWRG

Blueprint



Technical data

Part code	Code	Rope Ø range mm	Thread	No. of clips when lifting	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm	K mm	L mm	N mm	S mm	Weight kg
121100400090	PWRG-4	3-4	M5	3	5	25.2	11.2	13	6	8.4	4.8	23	8.6	5.5	13.8	20.4	11.5	28.6	8.2	0.05
121100600090	PWRG-6	5-6	M6	3	9	33	13.4	18.2	7.2	8.4	6.5	29.9	11.4	7.3	17.5	26.8	16.3	44.2	10.7	0.1
121100800090	PWRG-8	7-8	M6	3	12	35.2	14.2	17	6.5	8.3	8	32.3	12.5	7.6	22.6	27.8	16.3	44	10.7	0.14
121101000090	PWRG-10	9-10	M8	3	33	38.7	16.7	17.5	9	11	8.5	38.9	15.3	8.3	25.6	32.8	18.7	55	14	0.25
121101250090	PWRG-12	10-12.5	M8	3	33	45	16.3	20	9.1	10.7	10.8	42	15.5	10.8	30	35.5	18.7	55	13.7	0.32
121101650090	PWRG-16	13-16.5	M10	3	45	57.3	21.1	25.5	11.9	13.8	13.4	54.6	20.1	14.2	38.7	44.1	23.5	71.5	18.4	0.58
121102000090	PWRG-20	17-20	M12	3	75	63.8	27.9	34	14.6	16.4	14.4	59	24.6	13.8	45	54.3	34.6	87.5	18.5	0.95
121102500090	PWRG-25	21-25	M16	3	190	75.2	34.3	39.6	18.7	21.3	13.8	71.3	27.3	14.2	54.4	57.6	39.3	110	24.7	1.64
121103500090	PWRG-35	26-35	M16	4	277	97.5	46.9	58	20	30	22	104.6	36.8	19.7	65.5	88.2	55.8	160	25	3.7

Certex Polska
info@certex.pl
+48 91 817 28 49

© October 2026 - All Rights Reserved