Lifting Solutions Group
Axel Johnson International

Lifting Eye RUD VWBG-V

Product information



- Rotating 360°, pivoting 230°
- Indicator markings to highlight wear and damage to load ring
- Oversized load rings
- Ball bearing
- Variable bolt available on VWBG-V

... *Read more*

Marking: According to standard, CE-mark
Temperature range: -40°C up to +100°C
Standard: EN 1677-1, EN 1677-4

Safety factor: 4:1


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting Eye RUD VWBG-V

Blueprint



Technical data

Part code	WLL	Thread mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	M mm	T mm	Weight
42157103720	0.3	M8	8	31	29	30	27	13	36	M8	76	0.18
42157103715	0.45	M10	8	31	29	33.5	30	17	38	M10	78	0.29
42157100180	0.6	M12	10	49	35	42	36	21	47	M12	107	0.44
42157100800	2	M20	13	54	35	62	55	33	67	M20	137	1.42
42157100640	3.5	M24	18	66	40	81	70	40	88	M24	173	2.63
42157100650	5	M30	22	90	50	99	85	50	106	M30	221	5.09

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved