

## Lifting Eye RUD VWBG

---

### Product information



- Rotates 360°, pivots 230°
- Indicator markings to highlight wear and damage to load ring
- Oversized load rings
- Ball bearing

... [Read more](#)

---

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C up to +100°C


**Standard:** EN 1677-1, EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

## Lifting Eye RUD VWBG

### Blueprint



### Technical data

Part code	WLL	Thread mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	M mm	T mm	Weight
42157999059	8	M36	22	86	50	90	80	54	94	M36	208	4.72
42157999044	12	M42	26	111	65	98	85	63	95	M42	234	6.1
42157900455	12	M45	26	11	65	98	85	67	95	M45	234	6.24
42157999045	13	M48	26	111	65	98	85	68	95	M48	234	6.37
42157901081	14	M52	32	119	70	120	95	78	120	M52	271	10.55
42157999004	16	M56	32	119	70	120	95	84	120	M56	271	10.68
42157999043	16	M64	32	119	70	120	95	94	120	M64	271	11.4
42157900097	31.5	M72	46	130	90	170	145	108	159	M72	338	29.96