

Lifting Eye RUD VLBG-PLUS

Product information



VLBG load ring will turn 360°, adjustable in pull direction. Load ring foldable, full WLL in any load direction. ICE bolt made of Grade 120 material for higher resistance. DIN crack tested collared nut.

Also available in long version.

... [Read more](#)

Material: Forged high strength steel

Marking: According to standard, CE-marked, WLL


Finish: Striking fluorescent pink powder coating.

Standard: EN 1677-1

Safety factor: 4:1

Lifting Eye RUD VLBG-PLUS

Blueprint



Technical data

| Part code | Code | WLL ton | Thread | A mm | B mm | C mm | D mm | E mm | F mm | G mm | H mm | I mm | K mm | L mm | M mm | N mm | T mm | Weight kg |
|-------------|-----------|---------|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-----------|
| 42158504651 | VLBG-PLUS | 0.63 | M8 | 30 | 52 | 34 | 24 | 40 | 10 | 29 | 11 | 75 | 45 | 40 | M8 | 32 | 75 | 0.3 |
| 42158504652 | VLBG-PLUS | 0.9 | M10 | 30 | 54 | 34 | 24 | 39 | 10 | 29 | 15 | 75 | 45 | 44 | M10 | 32 | 75 | 0.31 |
| 42158504653 | VLBG-PLUS | 1.35 | M12 | 32 | 54 | 34 | 26 | 38 | 10 | 29 | 18 | 75 | 45 | 47 | M12 | 32 | 75 | 0.34 |
| 42158504655 | VLBG-PLUS | 2 | M16 | 34.5 | 56 | 38 | 30 | 39 | 13.5 | 36 | 22 | 86 | 47 | 58 | M16 | 38 | 85 | 0.55 |
| 42158504657 | VLBG-PLUS | 3.5 | M20 | 50 | 82 | 54 | 45 | 55 | 17 | 43 | 32 | 113 | 64 | 75 | M20 | 48 | 110 | 1.3 |
| 42158504659 | VLBG-PLUS | 4.5 | M24 | 50 | 82 | 54 | 45 | 67 | 17 | 43 | 37 | 130 | 78 | 80 | M24 | 48 | 125 | 1.4 |
| 42158504661 | VLBG-PLUS | 6.7 | M30 | 60 | 103 | 65 | 60 | 67 | 22.5 | 61 | 49 | 151 | 80 | 110 | M30 | 67 | 147 | 3.22 |
| 42158500829 | VLBG-PLUS | 7 | M36 | 60 | 103 | 65 | 60 | 74 | 22.5 | 55 | 52 | 151 | 80 | 107 | M36 | 67 | 146 | 3.4 |
| 42157983553 | VLBG-PLUS | 8 | M36 | 77 | 122 | 82 | 70 | 97 | 26.5 | 77 | 63 | 205 | 113 | 140 | M36 | 87 | 197 | 5.97 |
| 42157983554 | VLBG-PLUS | 10 | M42 | 77 | 122 | 82 | 70 | 94 | 26.5 | 77 | 73 | 205 | 113 | 150 | M42 | 79 | 196 | 6.6 |
| 42157982966 | VLBG-PLUS | 15 | M42 | 95 | 156 | 100 | 85 | 109 | 36 | 87 | 63 | 230 | 130 | 150 | M42 | 100 | 222 | 10.9 |
| 42157982967 | VLBG-PLUS | 20 | M48 | 95 | 156 | 100 | 95 | 105 | 36 | 87 | 73 | 230 | 130 | 160 | M48 | 100 | 222 | 11.6 |