

## ROV Hook RUD

---

### Product information



- The RUD ROV-HOOK eliminates the risk of snagging and accidental rigging.
- The outer profile is smooth with no protruding hook nose.
- Outwards opening safety latch.
- The safety latch automatically closes when the ROV releases the triggers.
- The safety latch is securely locked in closed position.
- The hook can be operated by all commonly used ROV manipulators, including the grabber.
- The hook safety latch opening and closing can be operated by a single ROV manipulator.
- The hook design minimises the time the ROV takes to carry out the attachment/detachment operation.

... [Read more](#)

---

**Material:** Steel

**Marking:** According to standard, CE-marked, WLL

**Temperature range:** -20°C up to 200°C

**Finish:** Painted

**Standard:** EN 1677-1

## ROV Hook RUD

### Technical data

| Part code    | Code              | WLL ton | A mm | B mm | C mm | D mm | E mm | F mm | F max mm | G mm | H mm | T mm | Weight kg |
|--------------|-------------------|---------|------|------|------|------|------|------|----------|------|------|------|-----------|
| 401301001030 | ROV-HOOK 2.0 10 t | 10      | 112  | 45   | 45   | 55   | 166  | 65   | 99       | 38   | 82   | 393  | 13.7      |
| 401302501030 | ROV-HOOK 2.0 25 t | 25      | 132  | 55   | 55   | 92   | 249  | 96   | 130      | 52   | 82   | 484  | 26        |