

Shortening Claw ICE IMVK

Product information



After decades of success, the VIP-Multi-Shortening claw has been further enhanced.

- Can be captively fitted along the chain leg.
- No additional chain and coupling components are required.
- It can be moved to any position along the chain leg.
- The ideal link shaped chain pocket provides an optimal fitting for the chain thus no reduction of the WLL.
- A robust safety bolt with a spring prevents the accidental loosening of the fitted chain in both loaded and unloaded conditions.

... [Read more](#)

Material: Steel

Marking: According to standard

Temperature range: -60°C up to 200°C

Finish: Painted

Standard: DIN 5692


Note: Detailed handling instructions are provided.

Safety factor: 4:1

Grade: 12

Shortening Claw ICE IMVK

Blueprint



Technical data

| Part code | Code | Chain diameter mm | WLL ton | A mm | B mm | C mm | D, mm | T mm | Weight kg |
|--------------|---------|-------------------|---------|------|------|------|-------|------|-----------|
| 403200180040 | IMVK 6 | 6 | 1.8 | 38 | 32 | 41 | 35 | 66 | 0.28 |
| 403200300040 | IMVK 8 | 8 | 3 | 47 | 40 | 54 | 47 | 88 | 0.61 |
| 403200500040 | IMVK 10 | 10 | 5 | 60 | 51 | 67 | 60 | 110 | 1.6 |
| 403200800040 | IMVK 13 | 13 | 8 | 77 | 65 | 87 | 77 | 143 | 2.6 |
| 403201250040 | IMVK 16 | 16 | 12.5 | 95 | 81 | 110 | 95 | 176 | 4.8 |