Lifting Solutions Group
Axel Johnson International

VIP Round Steel Link Chain RUD

Product information



The inhouse made special heat treatment gives the grade 100 round steel link chain a high toughness even at the high strength of the material. The chain is less sensitive regarding mechanical wear and damages which leads to a longer lifetime.

... *Read more*

Material: CrNiMo Steel
Marking: According to standard
Temperature range: -40°C up to 200°C
Finish: Fluorescent PINK® Powder Coating
Standard: EN 818

Safety factor: 4:1
Grade: 10


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

VIP Round Steel Link Chain RUD

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	Length m	A mm	B mm	T mm	Weight kg
203500401000190	4	0.63	100	4	5.2	12	0.38
203500400000190	4	0.63	-	4	5.2	12	0.38
203500602000190	6	1.5	200	6	7.8	18	0.91
203500600000190	6	1.5	-	6	7.8	18	0.91
203500801500190	8	2.5	150	8	10	24	1.57
203500800000190	8	2.5	-	8	10	24	1.57
203501001000190	10	4	100	10	13	30	2.45
203501000000190	10	4	-	10	13	30	2.45
203501300800190	13	6.7	80	13	17	39	4.04
203501300000190	13	6.7	-	13	17	39	4.04
203501600500190	16	10	50	16	21	48	6.02
203501600000190	16	10	-	16	21	48	6.02
203502000400190	20	16	40	20	26	60	9.79
203502000000190	20	16	-	20	26	60	9.79
203502200300190	22	20	30	22	29	66	12.31
203502200000190	22	20	-	22	29	66	12.31
203502800000190	28	31.5	-	28	37	84	18.6

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved