Lifting Solutions Group
Axel Johnson International

Wire rope Dyform Bristar 8

Product information



Dyform Bristar 8 is a high performance compacted single layer constructed rope which incorporates an engineered extruded plastic profile between the 8 outer strands and the rope core for cranes and industrial applications including mobile, crawler and tower cranes.

Standard: EN 12385-4
ISO 4309 Rope Category No: 10-17mm **RCN.04**, 18-34mm **RCN.09**, 36-50mm **RCN.11**

... *Read more*

Features: High breaking force.
Rope construction: 8x26
Material: High Carbon Steel
Marking: According to standard
Finish: Galvanised or Ungalvanised
Standard: EN 12385-4

Fill factor: 0.68
RCN: 04

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Wire rope Dyform Bristar 8

Technical data

Part code	Rope diameter mm	Tensile strength N/mm²	Finish	Rope lay	Min. breaking force kN	Lubrication	Weight kg/100m
103102804270659	28	1,960	Galvanized	sZ	691	SupplierStandard	367
103103203270709	32	1,960	Galvanized	zS	903	SupplierStandard	482
103103404270709	34	1,960	Galvanized	sZ	1,020	SupplierStandard	544
103103604270709	36	1,960	Galvanized	sZ	1,145	SupplierStandard	613
103103603270709	36	1,960	Galvanized	zS	1,145	SupplierStandard	613
103103804270709	38	1,960	Galvanized	sZ	1,300	SupplierStandard	685
103103803270709	38	1,960	Galvanized	zS	1,300	SupplierStandard	685

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved