Lifting Solutions Group
Axel Johnson International

General duty Thimble POWERTEX PT6899F

Product information



General duty Thimble PT6899F from POWERTEX, intended for general duty steel wire rope slings and synthetic rope end terminations.
Wire rope size 7 – 28 mm.

Standard: Generally according to DIN6899B

... *Read more*

Material: Forged steel
Marking: PX (Powertex), Recommended rope diameter, F (model)
Finish: Hot dip galvanized


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

General duty Thimble POWERTEX PT6899F

Blueprint



Technical data

Part code	Code	Rope Ø range mm	a mm	b mm	C mm	A mm	R1 mm	R2 mm	S mm	t mm	Weight kg
123100250430	PT6899F-2.5	2.5	3	4.5	12	19	1.5	2.2	1.6	4	0.005
123100350430	PT6899F-3.5	3.5	4	5.5	13	21	2	2.75	1.6	4.25	0.008
123100400430	PT6899F-4	4	5	6.5	14	23	2.5	3.25	1.9	4.5	0.01
123100500430	PT6899F-5	5	6	7.5	16	25	3	3.75	2.4	6.5	0.017
123100600430	PT6899F-6	6	7	8.5	18	28	3.5	4.25	2.4	7	0.021
123100700430	PT6899F-7	7	8	10	20	32	4	5	2.8	8	0.03
123100900430	PT6899F-9	9	10	12.5	24	38	5	6.25	3.1	8	0.05
123101100430	PT6899F-11	11	12	15	28	45	6	7.5	3.3	9.5	0.07
123101200430	PT6899F-12	12	13	16	30	48	6.5	8	3.3	10	0.08
123101300430	PT6899F-13	13	14	17.5	32	51	7	8.75	3.7	11	0.12
123101500430	PT6899F-15	15	16	20	36	58	8	10	3.8	12.5	0.16
123101600430	PT6899F-16	16	17	21	38	61	8.5	10.5	4.5	13	0.19
123101700430	PT6899F-17	17	18	22	40	64	9	11	4.7	13	0.21
123101800430	PT6899F-18	18	20	24.5	45	72	10	12.25	5.7	15	0.29
123102000430	PT6899F-20	20	22	27	50	80	11	13.5	5.7	16	0.38
123102200430	PT6899F-22	22	24	30	56	90	12	15	6.5	17	0.48
123102400430	PT6899F-24	24	26	33	62	99	13	16.5	6.8	21.5	0.59
123102600430	PT6899F-26	26	28	35	70	112	14	17.5	8	23	0.82
123102800430	PT6899F-28	28	30	37	75	120	15	18.5	8	25.5	1.1

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved