

## Ferrule STS Talurit®



### Product information

Ferrule for splicing of steel wire rope.

Typically carbon steel ferrules are used when corrosion, higher temperature and special dragging applications are used. This system is also an alternative to the flemish eye, this is due to the fact that you have all the benefits as above but the simplicity of a straight turnback system.

The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. It is far more efficient than all other swaging methods on the market.

**Material:** Carbon steel

**Marking:** According to standard

**Standard:** EN 13411-3

**Note:** See the manufacturer's product data sheet below for guidance on dimension selection.

Part code	Ferrule size mm	Length mm
120100500140	5	22
120100600140	6	26
120100700140	7	31
120100800140	8	34
120100900140	9	39
120101000140	10	43
120101100140	11	52
120101200140	12	57

120101300140	13	60
120101400140	14	69
120101600140	16	78
120101700140	17	62
120101800140	18	65
120102000140	20	73
120102200140	22	80
120102400140	24	87
120102800140	28	102
120103000140	30	109
120103400140	34	124
120103800140	38	139
120104200140	42	153
120104400140	44	161
120104800140	48	175
120105200140	52	190
120105600140	56	204
120106000140	60	219
120106400140	64	234
120106800140	68	248
120107200140	72	263
120107600140	76	278
120108400140	84	307

