Lifting Solutions Group
Axel Johnson International

Ferrule TK Talurit®

Product information



The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for fibre core, single layer wire ropes, steel core single layer wire ropes, rotation resistant wire ropes and some spiral strand ropes.

... Read more

Material: Aluminum.
Marking: According to standard
Standard: Talurit splicing system
The ferrules do not correspond to standard EN 13411-3 but have been tested and verified by Talurit.
Note: See the manufacturer's product data sheet below for guidance on dimension selection.

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Ferrule TK Talurit®

Technical data

Part code	Ferrule size mm	Length mm
120100800090	8	36
120100900090	9	40
120101000090	10	45
120101100090	11	50
120101200090	12	54
120101300090	13	59
120101400090	14	63
120101600090	16	72
120101800090	18	81
120102000090	20	90
120102200090	22	99
120102400090	24	108
120102600090	26	117
120102800090	28	126
120103000090	30	135
120103200090	32	144
120103400090	34	153
120103600090	36	162
120103800090	38	171
120104000090	40	180
120104400090	44	198
120104800090	48	216
120105200090	52	234
120105600090	56	252
120106000090	60	270

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved