Lifting Solutions Group
Axel Johnson International

Ferrule T-LOC Talurit®

Product information



T-LOC is designed for rotation resistant wire rope of grade 2160 together with T ferrules, especially in combination with solid thimble eyes.
When using high tensile wire rope of grade 2160, T-LOC will secure the special sling eye which has a higher splitting force than normal. Since T-LOC is produced from carbon steel and has a better tensile strength than aluminium.

... *Read more*

Material: Carbon steel
Marking: According to standard
Standard: EN 13411-3

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Ferrule T-LOC Talurit®

Technical data

Part code	Ferrule size mm
120101000160	10
120101100160	11
120101200160	12
120101300160	13
120101400160	14
120101600160	16
120101800160	18
120102000160	20
120102200160	22
120102400160	24
120102600160	26
120102800160	28
120103000160	30
120103200160	32
120103400160	34
120103600160	36
120103800160	38
120104000160	40
120104400160	44
120104800160	48
120105200160	52
120105600160	56
120106000160	60
120106600160	66
120107400160	74
120100900160	9

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved