
Lifting Solutions Group
Axel Johnson International

Steel Wire Rope Forest King

Product information



The most important advantage of ropes with such a construction construction is the excellent abrasion resistance of the outer surface of the rope and the significantly increased breaking strength of the rope, compared to the compared to a rope of standard design with, the same diameter. FOREST KING rope is proven ideal in the forest industry for skidding and timber transportation. ... *Read more*

Rope construction: 6xK26WS-IWRC
Marking: According to standard
Standard: EN 12385-4

Fill factor: 0,657
RCN: 06
Tolerance Ø: 0% to +5%

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Steel Wire Rope Forest King

Technical data

Part code	Rope diameter mm	Tensile strength N/mm²	Finish	Rope lay	Min. breaking force kN	Lubrication	Weight kg/m
103101004090990	10	2,060	Bright	sZ	104	Dry	0.57
103101104090990	11	2,060	Bright	sZ	123	Dry	0.7
103101204090990	12	2,060	Bright	sZ	144	Dry	0.83
103101304090990	13	2,060	Bright	sZ	165	Dry	0.98
103101404090990	14	2,060	Bright	sZ	188	Dry	1.15

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved