



## Heavy Duty Air Chain Hoists Red Rooster TMH (10.000, 15.000 & 20.000 kg)

### Product information

The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market. With M4 classification of mechanism this hoist is extremely reliable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a supporting eye for easy installation.

#### Standard features:

- Precise variable speed control (cord- and pendant control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

#### ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

#### Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

**Marking:** According to standard, CE-marked

**Standard:** EN 14492-2

Part code	WLL ton	Type	Chain falls	Lifting speed without load m/min	Air consumption lowering (l/sec)	Air consumption lifting l/sec	Lifting speed with max.load m/min	Lowering speed with max.load m/min	A, B, C, D, E, F, G, H, I J, K, L M N	Weight kg
									mm mmmm	
5601TMH10TC2	10	Cord control	2	3.3	71.7	58.3	1.6	3.2	860 46318827522160214266 315 65 ø60 45 351 ø61	206
5601TMH10TP2E	10	Pendant control	2	3.3	71.7	58.3	1.6	3.2	860 46318827522160214266 315 65 ø60 45 351 ø61	206
5601TMH15C3	15	Cord control	3	2.2	71.7	58.3	1.05	2.1	880 69563525527052250266 315 67 ø84 58 436 ø84	316
5601TMH15P3E	15	Pendant control	3	2.2	71.7	58.3	1.05	2.1	880 69563525527052250266 315 67 ø84 58 436 ø84	316
5601TMH20C4	20	Cord control	4	1.6	71.7	58.3	0.8	1.6	1,028500150350 - 64315326 387 80ø11078 475 ø110	466
5601TMH20P4E	20	Pendant control	4	1.6	71.7	58.3	0.8	1.6	1,028500150350 - 64315326 387 80ø11078 475 ø110	466

## Blueprint

