



Heavy Duty Air Chain Hoists Red Rooster TMH (37.500 & 45.000 kg)

Product information

The Red Rooster TMH series air chain hoists have the highest lifting speed with the lowest headroom on the hoist market.

Standard features:

- Precise variable speed control (cord control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (84 dBA)
- Working air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Marking: According to standard, CE-marked

Standard: EN 14492-2

Part code	WLL ton	Type	Chain falls	Lifting speed without load m/min	Air consumption lowering (l/sec)	Air consumption lifting l/sec	Lifting speed with max.load m/min	Lowering speed with max.load m/min	A, B, C, D, E, F, G, H, I, J, K, L, M, N, O, P, Q	Weight kg
5601TMH375TC3	37.5	Cord control	3	1.8	180	108	0.9	2	1,440,1,150,557.5,592.5,118,908,30,380,675,125,118,545,352,256,112,112,300	1,300
5601TMH375TP3E	37.5	Pendant control	3	1.8	180	108	0.9	2	1,440,1,150,557.5,592.5,118,908,30,380,675,125,118,545,352,256,112,112,300	1,300
5601TMH45TC3	45	Cord control	3	1.8	167	108	0.65	1.8	1,440,1,150,557.5,592.5,118,908,30,380,675,125,118,545,352,256,112,112,300	1,300
5601TMH45TP3E	45	Pendant control	3	1.8	167	108	0.65	1.8	1,440,1,150,557.5,592.5,118,908,30,380,675,125,118,545,352,256,112,112,300	1,300

Blueprint

