



## Welded Master Link X-002

### Product information

Welded Master Link designed for 1-2 legs Wire Rope and Chain Slings. The engineered flat makes it simple to insert wire rope thimbles on our links. Suitable for omega links.

At least 25% greater WLL than traditional Grade 8 products.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Tempering temperature at a minimum of 400°C.

**Material:** Quenched and Tempered Alloy Steel.

**Marking:** According to standard, CE-marked, Type, manufacturer ID, traceability.

**Temperature range:** -40° up to +200°C (without reduction in WLL).

**Finish:** Blue painted.

**Standard:** EN 1677-4

**Safety factor:** 4:1

**Grade:** 10

Part code	Code	WLL ton	EWL mm	For chain, 1-leg mm	For chain, 2-leg mm	A mm	B mm	D, mm	Weight kg
402100280420	BD-13	2.8	110	7,8	6	110	60	13	0.3
402100400420	BD-16	4	110	10	7,8	110	60	16	0.5
402100670420	BD-19	6.7	135	13	10	135	75	19	0.9
402100850420	BD-22	8.5	160	13	10	160	90	22	1.5
402101150420	BD-28	11.5	180	16	13	180	100	28	2.7
402101700420	BD-32	17	200	20	16	200	110	32	3.9
402102510420	BD-36	25.1	260	22	20	260	140	36	6.3
402103830420	BD-45	38.3	300	26	22	300	180	45	11.8
402104500420	BD-50	45	300	32	26	300	200	50	15.2

## Blueprint

