



Welded Master Link X-002

Product information

Welded Master Link designed for 1-2 legs Wire Rope and Chain Slings. The engineered flat makes it simple to insert wire rope thimbles on our links. Suitable for omega links.

At least 25% greater WLL than traditional Grade 8 products.

Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Tempering temperature at a minimum of 400°C.

Material: Quenched and Tempered Alloy Steel.

Marking: According to standard, CE-marked, Type, manufacturer ID, traceability.

Temperature range: -40° up to +200°C (without reduction in WLL).

Finish: Blue painted.

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part Code	Code	WLL ton	For chain gr 10 Ø 2 leg mm	For chain gr 10 Ø 1 leg mm	A mm	B mm	D mm	Weight kg
42050327B	BD-13	2.8	6	7,8	110	60	13	0.3
42050328B	BD-16	4	7,8	10	110	60	16	0.5
42050329B	BD-19	6.7	10	13	135	75	19	0.9
42050330B	BD-22	8.5	10	13	160	90	22	1.5
42050331B	BD-28	11.5	13	16	180	100	28	2.7
42050332B	BD-32	17	16	20	200	110	32	3.9
42050333B	BD-36	25.1	20	22	260	140	36	6.3
42050334B	BD-45	38.3	22	26	300	180	45	11.8
42050335B	BD-50	45	32	28	300	200	50	15.2

Blueprint

