Lifting Solutions Group
Axel Johnson International

Enlarged Welded Master Link Assembly X-007

Product information



Welded Master Link designed for 3-4 legs Wire Rope and Chain Slings.

At least 25% greater WLL than traditional Grade 8 products.
Proof Load tested at 2.5 times the WLL with certification for each batch manufactured. Fatigue rated to 20,000 cycles at 1.5 times the WLL.

... *Read more*

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, CE-mark, Type, manufacturer ID, traceability.
Temperature range: -40° up to +200°C (without reduction in WLL).
Finish: Blue painted
Standard: EN 1677-4

Safety factor: 5:1
Grade: 10


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Enlarged Welded Master Link Assembly X-007

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	Proof Load kN	Can be used up to single hook acc. to DIN 15401 no.	D mm	A mm	B mm	d mm	a mm	b mm	Weight kg
402100530530	7-8	5.3	130	6	19	160	90	16	140	70	2.4
402100890530	10	8.9	218	16	25	275	145	19	160	90	5.2
402101290530	10	12.9	316	16	28	275	145	22	180	100	7.1
402101700530	13	17	417	16	32	275	145	25	210	115	10
402102360530	16	23.6	578	16	36	275	145	28	190	100	12.2
402102810530	16	28.1	688	20	40	300	160	32	275	145	19.2
402103830530	20	38.3	938	25	45	340	180	36	285	155	26.5

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Enlarged Welded Master Link Assembly X-007

Assembled with		
AD-19	+	2 AD-161
AD-251	+	2 AD-19
AD-28	+	2 AD-22
AD-32	+	2 AD-25
AD-361	+	2 AD-281
AD-40	+	2 AD-32
AD-45	+	2 AD-36
AD-50	+	2 AD-401
AD-60	+	2 AD-50
AD-70	+	2 AD-601
AD-90	+	2 AD-701

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved