Lifting Solutions Group
Axel Johnson International

Connecting Link X-015 Grade 10

Product information



- At least 25% greater WLL than traditional Grade 8 products.
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Suitable for use with both Grade 8 and Grade 10 chain.

When fitting G10 components are added to G8 chain, the sling is rated at G8 WLL

... Read more

Material: Quenched and Tempered Alloy Steel.
Marking: According to standard, Type, manufacturer ID, traceability.
Temperature range: -40° up to +200°C (without reduction in WLL).
Finish: Blue painted.
Standard: EN 1677-1

Safety factor: 4:1
Grade: 10


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Connecting Link X-015 Grade 10

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	EWL mm	A mm	B mm	D mm	K mm	Weight kg
402200140190	6	1.4	45	15	17	7	45	0.08
402200250190	7-8	2.5	59	18	23	9	59	0.2
402200400190	10	4	69	25	27	11	69	0.3
402200670190	13	6.7	92	30	37	16	92	0.7
402201000190	16	10	101	36	39	19	101	1.2
402201600190	20	16	122	42	46	23	122	2.1
402201900190	22	19	152	49	59	24	152	3.5
402202650190	26	26.5	162	55	62	30	162	4.8
402204000190	32	40	203	69	79	36	203	9

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved