



## Eye Point Stainless Steel 8-S291

### Product information

- Rotates through 360° adjustable in the direction of the load.
- Individual forged parts and cap screw are traceable to Test Certification.
- Bolts are Metric thread.
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Quick and simple assembly, just a tapped hole is required.
- Used in different applications such as chemical oil coal industries, food processing,

**Material:** Stainless Steel

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1

**Safety factor:** 4:1

**Grade:** 10

Part Code	WLL ton	Torque Nm	Thread M mm	Thread length (E) mm	Pitch DIN13	A mm	B mm	C mm	D mm	F mm	G mm	H mm	J mm	S mm	W mm	Weight kg
11.428-S291-005	0.5	10	M12	18	1.75	45	30	10	11	33	29	5	44	8	52	0.2
11.428-S291-010	1	30	M16	24	2	52	35	14	13	35	33	5	51	10	61	0.3
11.428-S291-020	2	70	M20	30	2.5	60	40	16	15	44	37	7	60	12	70	0.6
11.428-S291-025	2.5	150	M24	36	3	72	49	19	18	52	46	10	72	14	84	1

## Blueprint

