



## Air Chain Hoists Red Rooster TMH-series (3.000 - 15.000 kg)

### Product information

With M4 classification of mechanism this hoist is extremely reliable. This hoist will guarantee the continuity of your process. The TMH hoists are designed with a full load supporting eye for installation and securing (during lift applications) the hoist for extra safety.

#### Standard features:

- Precise variable speed control (cord- and pendant control)
- Optimum control of the load, very precise positioning
- Main air shut off valve
- Mechanical end stop system
- Load limiter built-in without loss of headroom
- Low noise level (80 dBA)
- Air pressure 0,4 - 0,63 MPa (4-6,3 bar)
- Piped away exhaust air

#### Optional features:

- Marine Specification/Corrosion resistant
- Paint systems from C2 - Industrial to C5 - Offshore specification (Red finish as standard. Other RAL colours available on request)
- Choice of pendants
- Radio control pendant for electro pneumatic controls
- Control systems
- Chain collectors (PVC, galvanised or stainless steel)
- Various types of hook or clevis available
- Air supply systems and valves
- Piped away exhaust air
- In house design for "specials"
- Festoon systems
- Main air shut off valve

#### ATEX:

- According to EC Directive 94/9/EC (Ex Classification)

#### Recommended:

We strongly recommend using an air handling unit, e.g. from SMC (offered separately).

Marking: According to standard, CE-marked

Standard: EN 14492-2

Part code	Code	WLL ton	Number of falls	Lifting speed without load m/min	Air consumption lifting (l/sec)	Lifting speed with load m/min	Lowering speed with load m/min	Air consumption lowering (l/sec)	A, B, C, D, E, F, H I	Weight Ø mm kg
5601TMH3000C	TMH-3000C	3	1	10.8	56	5.4	10.2	68	537 314 189 125 26531150 34	99
5601TMH3000PE	TMH-3000PE	3	1	10.8	56	5.4	10.2	68	537 314 189 125 265311 - -	99
5601TMH6000C2	TMH-6000C2	6	2	5.4	56	2.7	5.1	68	742 371 245 126 26531165 42	124
5601TMH6000P2E	TMH-6000P2E	6	2	5.4	56	2.7	5.1	68	742 371 245 126 26531165 42	124
5601TMH9000C3	TMH-9000C3	9	3	3.6	56	1.8	3.4	68	783 455 160 295 26531175 53	170
5601TMH9000P3E	TMH-9000P3E	9	3	3.6	56	1.8	3.4	68	783 455 160 395 26531175 53	170
5601TMH12000C4	TMH-12000C4	12	4	2.7	56	1.35	2.5	68	856398.5149.5 249 30926683 64	190
5601TMH12000P4E	TMH-12000P4E	12	4	2.7	56	1.35	2.5	68	856398.5149.5 249 30926683 64	190
5601TMH15000C5	TMH-15000C5	15	5	2.16	56	1.08	2.04	68	855 466 152.5313.530027583 58	280
5601TMH15000P5E	TMH-15000P5E	15	5	2.16	56	1.08	2.04	68	855 466 152.5313.530027584 58	280

## Technical data

# Blueprint

