Lifting Solutions Group
Axel Johnson International

# Black Belt Sling™ Extreema® with HMPE core

**Product information**



These Extreema® HMPE soft slings have an extensive track record and a solid global footprint in the heavy lift industry. The Black Belt Sling™ has unparalleled load-bearing capacity, ensuring the safe and efficient lifting of even the heaviest loads.

The core is made of general HMPE (Trosar®), which makes it up to 15 times stronger than steel on a weight-to-weight basis.

The sleeve is an orange PES inner sleeve and is covered with a black knitted Cordura® outer sleeve, which is known for its resistance to abrasions, tears, and scuffs. The black sleeve is repairable.

**When to choose this product**

**Best for:**

- Heavy lifting with cranes, shackles, and large connection points
- Environments with high abrasion and repeated handling

**Features:**

- Lightweight and flexible, easy to handle
- Repairable sleeve
- Does not absorb water
- Floats on water
- Abrasion, tearing and scuff resistant
- Sustainable
- High pressure resistant
- EWL: 0,5m – 65m
- Standard with RFID

... *Read more*

**Material:** PES, Dyneema
**Marking:** CE-marked
**Temperature range:** -40°C up to +70°C

**Safety factor:** 7:1

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Black Belt Sling™ Extreema® with HMPE core

## Technical data

| Part code | WLL ton | EWL m |
|---|---|---|
| 340501000500140 | 10 | 5 |
| 340503001800140 | 30 | 18 |
| 340504000200140 | 40 | 2 |
| 340504000600140 | 40 | 6 |
| 340504000400140 | 40 | 4 |
| 340505000600140 | 50 | 6 |
| 340505000300140 | 50 | 3 |
| 340505000600142 | 50 | 6 |
| 340507500050140 | 75 | 0.5 |
| 340507500480140 | 75 | 4.82 |
| 340508000410140 | 80 | 4.1 |
| 340508000440140 | 80 | 4.4 |
| 340508500100140 | 85 | 1 |
| 340508500200140 | 85 | 2 |
| 340508500300140 | 85 | 3 |
| 340508500400140 | 85 | 4 |
| 340508500870140 | 85 | 8.7 |
| 340510000500140 | 100 | 5 |
| 340510000600140 | 100 | 6 |
| 340510001000140 | 100 | 10 |
| 340510001200140 | 100 | 12 |
| 340512000200140 | 120 | 2 |
| 340512000700140 | 120 | 7 |
| 340512500200140 | 125 | 2 |
| 340512500400140 | 125 | 4 |
| 340515001500140 | 150 | 15 |
| 340516000700140 | 160 | 7 |
| 340518000500140 | 180 | 5 |
| 340518000600140 | 180 | 6 |
| 340520001000140 | 200 | 10 |
| 340520000600140 | 200 | 6 |

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Black Belt Sling™ Extreema® with HMPE core

## Technical data

| Part code | WLL<br>ton | EWL<br>m |
|---|---|---|
| 340520000400140 | 200 | 4 |
| 340525000300140 | 250 | 3 |
| 340525000500140 | 250 | 5 |
| 340525000700140 | 250 | 7 |
| 340525000800140 | 250 | 8 |

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved