CERTEX | Lifting Solutions Group
Axel Johnson International

# Inferno® Soft Sling

**Product information**



The Black Inferno® sling is a heat resistant lifting sling designed for demanding lifting tasks where elevated temperatures and controlled handling are required. Manufactured from high-performance aramid materials, it maintains lifting capability in environments where standard slings would degrade. Its matte black version is suited for entertainment and stage rigging where low visibility is required.

WLL range: 2t – 50t (black version up to 2.5t)
EWL range: 0,5m – 16m

**When to choose this product**

**Best for:**

- Lifting operations exposed to heat up to 200°C
- Entertainment, theatre, and stage rigging requiring low visibility

**Product benefits**

- Aramid construction maintains strength at elevated temperatures up to 200°C
- Soft and lightweight design improves handling and positioning accuracy
- Low D:d ratio supports use with smaller diameter lifting points
- High abrasion resistance extends service life in repeated use
- Matte black finish reduces visual impact in stage and event environments

... *Read more*

**Material:** 100% Aramid
**Marking:** According to standard, CE-marked, UKCA-marked
**Temperature range:** Up to +200°C
**Standard:** EN 1492-2
*except material*
**Warning:** Slings should be protected from edges, friction and abrasion, whether from the load or the lifting appliance. Where reinforcements and protection against damage from edges and/or abrasion is supplied as part of the sling, this should be correctly positioned. It may be necessary to supplement this with additional protection.

**Safety factor:** 7:1

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Inferno® Soft Sling

## Technical data

| Part code | WLL ton | EWL m | Colour |
|---|---|---|---|
| 340500300050110 | 3 | 0.5 | Yellow |
| 340500300100110 | 3 | 1 | Yellow |
| 340500300200110 | 3 | 2 | Yellow |
| 340500300300110 | 3 | 3 | Yellow |
| 340500300400110 | 3 | 4 | Yellow |
| 340500300500110 | 3 | 5 | Yellow |
| 340500500050110 | 5 | 0.5 | Yellow |
| 340500500100110 | 5 | 1 | Yellow |
| 340500500200110 | 5 | 2 | Yellow |
| 340500500300110 | 5 | 3 | Yellow |
| 340500500400110 | 5 | 4 | Yellow |
| 340500500500110 | 5 | 5 | Yellow |
| 340501000050110 | 10 | 0.5 | Yellow |
| 340501000100110 | 10 | 1 | Yellow |
| 340501000200110 | 10 | 2 | Yellow |
| 340501000300110 | 10 | 3 | Yellow |
| 340501000400110 | 10 | 4 | Yellow |
| 340501000500110 | 10 | 5 | Yellow |

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved