

Direct VIP chain connection PowerPoint® WPPH-VIP



Product information

Universal connection with many attachment options.













- ideal connection link for crossbars construction
- clear marking of the minimum WLL
- compact design

Marking: WLL

Safety factor: 4:1

| Part code | Code | WLL ton | T mm | A mm | D mm | Weight kg |
|-------------|------------------|------------|---------|------|---------|--------------|
| 42157989982 | WPPH-VIP4-0,63t | 0.63 | 34 | 4 | 34 | 0.17 |
| 42157989983 | WPPH-VIP6-1,5t | 1.5 | 44 | 6 | 40 | 0.33 |
| 42157989984 | WPPH-VIP8-2,5t | 2.5 | 53 | 8 | 53 | 0.74 |
| 42157989985 | WPPH-VIP10-4t | 4 | 66 | 10 | 68 | 1.47 |
| 42157989986 | WPPH-VIP13-5t | 5 | 79 | 13 | 83 | 2.65 |
| 42157989987 | WPPH-VIP16-8t | 8 | 88 | 16 | 88 | 3.5 |
| 42157903438 | WPPH-KA-28-31,5t | 31.5 | 81 | 28 | 148 | 12.1 |

Technical data

| Method of lift |  |  |  |  |  |  |  |  | | |
|---|---|---|---|---|--|---|---|---|-----------------------|----------------------|
| Lifting from the side | Attention, when lifting point is attached to the side the max. inclination angle β can only be 25° / resp. until lifting means touches load (compare 4.2, 6)! | | | |  |  |  |  | | |
| Number of legs | 1 | 1 | 2 | 2 | 2 | 2 | 2 | 3 & 4 | 3 & 4 | 3 & 4 |
| Angle of inclination β | 0° | 90° | 0° | 90° | 0-45° | 45-60° | unsymm. | 0-45° | 45-60° | unsymm. |
| Factor | 1 | 1 | 2 | 2 | 1.4 | 1 | 1 | 2.1 | 1.5 | 1 |
| Type | Max. weight of load >G< in metric tons for all PowerPoint types with different sling methods | | | | | | | | | |
| WPP / WPPH - ... - 0.63 t | 0.63 t (1385 lbs) | 0.63 t (1385 lbs) | 1.26 t (2770 lbs) | 1.26 t (2770 lbs) | 0.88 t (1940 lbs) | 0.63 t (1385 lbs) | 0.63 t (1385 lbs) | 1.32 t (2900 lbs) | 0.95 t (2080 lbs) | 0.63 t (1385 lbs) |
| WPP / WPPH - ... - 1.5 t | 1.5 t (3300 lbs) | 1.5 t (3300 lbs) | 3.0 t (6600 lbs) | 3.0 t (6600 lbs) | 2.1 t (4620 lbs) | 1.5 t (3300 lbs) | 1.5 t (3300 lbs) | 3.15 t (6930 lbs) | 2.25 t (4950 lbs) | 1.5 t (3300 lbs) |
| WPP / WPPH - ... - 2.5 t | 2.5 t (5500 lbs) | 2.5 t (5500 lbs) | 5.0 t (11000 lbs) | 5.0 t (11000 lbs) | 3.5 t (7700 lbs) | 2.5 t (5500 lbs) | 2.5 t (5500 lbs) | 5.25 t (11550) | 3.75 t (8250 lbs) | 2.5 t (5500 lbs) |
| WPP / WPPH - ... - 4 t | 4.0 t (8800 lbs) | 4.0 t (8800 lbs) | 8.0 t (17600 lbs) | 8.0 t (17600 lbs) | 5.6 t (12320 lbs) | 4.0 t (8800 lbs) | 4.0 t (8800 lbs) | 8.4 t (18480 lbs) | 6.0 t (13200 lbs) | 4.0 t (8800 lbs) |
| WPP / WPPH - ... - 5 t | 6.7 t (15000 lbs) | 5.0 t (11000 lbs) | 13.4 t (30000 lbs) | 10.0 t (22000 lbs) | 7.0 t (15400 lbs) | 5.0 t (11000 lbs) | 5.0 t (11000 lbs) | 10.5 t (23100 lbs) | 7.5 t (16500 lbs) | 5.0 t (11000 lbs) |
| WPP / WPPH - ... - 8 t | 10.0 t (22000 lbs) | 8.0 t (17600 lbs) | 20.0 t (44000 lbs) | 16.0 t (35200 lbs) | 11.2 t (24640 lbs) | 8.0 t (17600 lbs) | 8.0 t (17600 lbs) | 16.8 t (36960 lbs) | 12.0 t (26400 lbs) | 8.0 t (17600 lbs) |

Blueprint

