

## Direct VIP chain connection PowerPoint® WPPH-VIP



### Product information

Universal connection with many attachment options.

















- ideal connection link for crossbars construction
- clear marking of the minimum WLL
- compact design

**Marking:** WLL

**Safety factor:** 4:1

Part code	Code	WLL ton	T mm	A mm	D, mm	Weight kg
42157989982	WPPH-VIP4-0,63t	0.63	34	4	34	0.17
42157989983	WPPH-VIP6-1,5t	1.5	44	6	40	0.33
42157989984	WPPH-VIP8-2,5t	2.5	53	8	53	0.74
42157989985	WPPH-VIP10-4t	4	66	10	68	1.47
42157989986	WPPH-VIP13-5t	5	79	13	83	2.65
42157989987	WPPH-VIP16-8t	8	88	16	88	3.5
42157903438	WPPH-KA-28-31,5t	31.5	81	28	148	12.1

## Technical data

Method of lift										
<b>Lifting from the side</b>	Attention, when lifting point is attached to the side the max. inclination angle $\beta$ can only be 25° / resp. until lifting means touches load (compare 4.2, 6)!									
<b>Number of legs</b>	1	1	2	2	2	2	2	3 & 4	3 & 4	3 & 4
<b>Angle of inclination <math>\beta</math></b>	0°	90°	0°	90°	0-45°	45-60°	unsymm.	0-45°	45-60°	unsymm.
<b>Factor</b>	1	1	2	2	1.4	1	1	2.1	1.5	1
<b>Type</b>	<b>Max. weight of load &gt;G&lt; in metric tons for all PowerPoint types with different sling methods</b>									
WPP / WPPH - ... - 0.63 t	0.63 t (1385 lbs)	0.63 t (1385 lbs)	1.26 t (2770 lbs)	1.26 t (2770 lbs)	0.88 t (1940 lbs)	0.63 t (1385 lbs)	0.63 t (1385 lbs)	1.32 t (2900 lbs)	0.95 t (2080 lbs)	0.63 t (1385 lbs)
WPP / WPPH - ... - 1.5 t	1.5 t (3300 lbs)	1.5 t (3300 lbs)	3.0 t (6600 lbs)	3.0 t (6600 lbs)	2.1 t (4620 lbs)	1.5 t (3300 lbs)	1.5 t (3300 lbs)	3.15 t (6930 lbs)	2.25 t (4950 lbs)	1.5 t (3300 lbs)
WPP / WPPH - ... - 2.5 t	2.5 t (5500 lbs)	2.5 t (5500 lbs)	5.0 t (11000 lbs)	5.0 t (11000 lbs)	3.5 t (7700 lbs)	2.5 t (5500 lbs)	2.5 t (5500 lbs)	5.25 t (11550)	3.75 t (8250 lbs)	2.5 t (5500 lbs)
WPP / WPPH - ... - 4 t	4.0 t (8800 lbs)	4.0 t (8800 lbs)	8.0 t (17600 lbs)	8.0 t (17600 lbs)	5.6 t (12320 lbs)	4.0 t (8800 lbs)	4.0 t (8800 lbs)	8.4 t (18480 lbs)	6.0 t (13200 lbs)	4.0 t (8800 lbs)
WPP / WPPH - ... - 5 t	6.7 t (15000 lbs)	5.0 t (11000 lbs)	13.4 t (30000 lbs)	10.0 t (22000 lbs)	7.0 t (15400 lbs)	5.0 t (11000 lbs)	5.0 t (11000 lbs)	10.5 t (23100 lbs)	7.5 t (16500 lbs)	5.0 t (11000 lbs)
WPP / WPPH - ... - 8 t	10.0 t (22000 lbs)	8.0 t (17600 lbs)	20.0 t (44000 lbs)	16.0 t (35200 lbs)	11.2 t (24640 lbs)	8.0 t (17600 lbs)	8.0 t (17600 lbs)	16.8 t (36960 lbs)	12.0 t (26400 lbs)	8.0 t (17600 lbs)

# Blueprint

