Lifting Solutions Group
Axel Johnson International

Multi Shortening Claw RUD VIP VMVK

Product information



- Can be captively fitted along the chain leg.
- No additional chain and coupling components are required.
- Can be moved to any position along the chain leg.
- The ideal link shaped chain pocket provides an optimal fitting for the chain thus no reduction of the WLL.
- A robust safety bolt with a spring prevents the accidental loosening of the fitted chain in both loaded and unloaded conditions.
- Detailed handling instructions are provided.

... *Read more*

Material: Steel
Marking: According to standard
Temperature range: -40°C up to 200°C
Standard: DIN 5692

Safety factor: 4:1


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Multi Shortening Claw RUD VIP VMVK

Blueprint



Technical data

Part code	Code	WLL ton	A mm	B mm	C mm	D mm	T mm	Weight kg
402200150400	VMVK-6	1.5	34	30	40	35	66	0.24
402200250400	VMVK-8	2.5	48	40	54	48	88	0.61
402200400400	VMVK-10	4	60	49	67	60	110	1.21
402200670400	VMVK-13	6.7	74	64	86	76	143	2.35
402201000400	VMVK-16	10	91	79	105	98	176	4.38

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved