

Ring Connection PowerPoint® WPPH-B

Product information

Connection link for crossbars construction. Compact design.

Marking: WLL

Safety factor: 4:1

Part code	WLL ton	A mm	B mm	T mm	C mm	D mm	G mm	N mm	Weight kg
42157989976	0.63	9	65	99	35	34	34	15	0.15
42157989977	1.5	11	65	109	35	40	44	15	0.3
42157989978	2.5	13	74	127	40	53	53	18	0.9

Technical data

Method of lift	Ğ	G G G		G B	G G		G	G		G	
Lifting from the side	the max. inc	lination angle	int is attached B can only b s load (compa	e 25° / resp.	β max. 25°	X	<u></u>	β max. 25°	X	4	
Number of legs	7	1	2	2	2	2	~~~~	3 & 4	3 & 4	3 & 4	
Angle of inclination <ß	0°	90°	0°	90°	0-45°	45-60°	unsymm.	0-45°	45-60°	unsymm.	
Factor	1	1	2	2	1.4	1	1	2.1	1.5	1	
Туре	Max. weight of load >G< in metric tons for all PowerPoint types with different sling methods										
WPP / WPPH	0.63 t	0.63 t	1.26 t	1.26 t	0.88 t	0.63 t	0.63 t	1.32 t	0.95 t	0.63 t	
0.63 t	(1385 lbs)	(1385 lbs)	(2770 lbs)	(2770 lbs)	(1940 lbs)	(1385 lbs)	(1385 lbs)	(2900 lbs)	(2080 lbs)	(1385 lbs)	
WPP / WPPH	1.5 t	1.5 t	3.0 t	3.0 t	2.1 t	1.5 t	1.5 t	3.15 t	2.25 t	1.5 t	
1.5 t	(3300 lbs)	(3300 lbs)	(6600 lbs)	(6600 lbs)	(4620 lbs)	(3300 lbs)	(3300 lbs)	(6930 lbs)	(4950 lbs)	(3300 lbs)	
WPP / WPPH	2.5 t	2.5 t	5.0 t	5.0 t	3.5 t	2.5 t	2.5 t	5.25 t	3.75 t	2.5 t	
2.5 t	(5500 lbs)	(5500 lbs)	(11000 lbs)	(11000 lbs)	(7700 lbs)	(5500 lbs)	(5500 lbs)	(11550)	(8250 lbs)	(5500 lbs)	
WPP / WPPH	4.0 t	4.0 t	8.0 t	8.0 t	5.6 t	4.0 t	4.0 t	8.4 t	6.0 t	4.0 t	
4 t	(8800 lbs)	(8800 lbs)	(17600 lbs)	(17600 lbs)	(12320 lbs)	(8800 lbs)	(8800 lbs)	(18480 lbs)	(13200 lbs)	(8800 lbs)	
WPP / WPPH	6.7 t	5.0 t	13.4 t	10.0 t	7.0 t	5.0 t	5.0 t	10.5 t	7.5 t	5.0 t	
5 t	(15000 lbs)	(11000 lbs)	(30000 lbs)	(22000 lbs)	(15400 lbs)	(11000 lbs)	(11000 lbs)	(23100 lbs)	(16500 lbs)	(11000 lbs)	
WPP / WPPH	10.0 t	8.0 t	20.0 t	16.0 t	11.2 t	8.0 t	8.0 t	16.8 t	12.0 t	8.0 t	
8 t	(22000 lbs)	(17600 lbs)	(44000 lbs)	(35200 lbs)	(24640 lbs)	(17600 lbs)	(17600 lbs)	(36960 lbs)	(26400 lbs)	(17600 lbs)	

Blueprint

