

Ring Connection PowerPoint® WPPH-B



Product information

















Connection link for crossbars construction. Compact design.

Marking: WLL

Safety factor: 4:1

Part code	WLL ton	A mm	B mm	T mm	C mm	D, mm	G, mm	Nmm mm	Weight kg
42157989976	0.63	9	65	99	35	34	34	15	0.15
42157989977	1.5	11	65	109	35	40	44	15	0.3
42157989978	2.5	13	74	127	40	53	53	18	0.9

Technical data

Method of lift										
Lifting from the side	Attention, when lifting point is attached to the side the max. inclination angle β can only be 25° / resp. until lifting means touches load (compare 4.2, 6)!									
Number of legs	1	1	2	2	2	2	2	3 & 4	3 & 4	3 & 4
Angle of inclination β	0°	90°	0°	90°	0-45°	45-60°	unsymm.	0-45°	45-60°	unsymm.
Factor	1	1	2	2	1.4	1	1	2.1	1.5	1
Type	Max. weight of load >G< in metric tons for all PowerPoint types with different sling methods									
WPP / WPPH - ... - 0.63 t	0.63 t (1385 lbs)	0.63 t (1385 lbs)	1.26 t (2770 lbs)	1.26 t (2770 lbs)	0.88 t (1940 lbs)	0.63 t (1385 lbs)	0.63 t (1385 lbs)	1.32 t (2900 lbs)	0.95 t (2080 lbs)	0.63 t (1385 lbs)
WPP / WPPH - ... - 1.5 t	1.5 t (3300 lbs)	1.5 t (3300 lbs)	3.0 t (6600 lbs)	3.0 t (6600 lbs)	2.1 t (4620 lbs)	1.5 t (3300 lbs)	1.5 t (3300 lbs)	3.15 t (6930 lbs)	2.25 t (4950 lbs)	1.5 t (3300 lbs)
WPP / WPPH - ... - 2.5 t	2.5 t (5500 lbs)	2.5 t (5500 lbs)	5.0 t (11000 lbs)	5.0 t (11000 lbs)	3.5 t (7700 lbs)	2.5 t (5500 lbs)	2.5 t (5500 lbs)	5.25 t (11550)	3.75 t (8250 lbs)	2.5 t (5500 lbs)
WPP / WPPH - ... - 4 t	4.0 t (8800 lbs)	4.0 t (8800 lbs)	8.0 t (17600 lbs)	8.0 t (17600 lbs)	5.6 t (12320 lbs)	4.0 t (8800 lbs)	4.0 t (8800 lbs)	8.4 t (18480 lbs)	6.0 t (13200 lbs)	4.0 t (8800 lbs)
WPP / WPPH - ... - 5 t	6.7 t (15000 lbs)	5.0 t (11000 lbs)	13.4 t (30000 lbs)	10.0 t (22000 lbs)	7.0 t (15400 lbs)	5.0 t (11000 lbs)	5.0 t (11000 lbs)	10.5 t (23100 lbs)	7.5 t (16500 lbs)	5.0 t (11000 lbs)
WPP / WPPH - ... - 8 t	10.0 t (22000 lbs)	8.0 t (17600 lbs)	20.0 t (44000 lbs)	16.0 t (35200 lbs)	11.2 t (24640 lbs)	8.0 t (17600 lbs)	8.0 t (17600 lbs)	16.8 t (36960 lbs)	12.0 t (26400 lbs)	8.0 t (17600 lbs)

Blueprint

