Lifting Solutions Group
Axel Johnson International

Shackle RUD VIP Foolproof

Product information



- High tensile version with an integrated safety thread in the shackle bracket. Smooth bolt support in the shackle on both sides.
- The bolt is turnable. No bending strength in the thread (only a securing function). Long term securing by driving in the pre-assembled tensioning sleeve.
- Special thread, thus distinctive in comparison to other shackle bolts.
- incl. RUD ID-POINT (from nominal size 10)

... *Read more*

Temperature range: -40°C up to 200°C

Safety factor: 4:1
Grade: 10


Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Shackle RUD VIP Foolproof

Blueprint



Technical data

Part code	Code	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	T mm	Weight kg
420100151870	VV-SCH-6	1.5	14	8	22	10	8	17	36	30	0.09
420100251870	VV-SCH-8	2.5	17	10	26	12	10	19	44	36	0.17
420100401870	VV-SCH-10	4	21	13	34	16	13	24	56	49	0.4
420100671870	VV-SCH-13	6.7	27	17	42	20	17	29	75	63	0.8
420101001870	VV-SCH-16	10	33	21	49	24	21	36	90	73	1.34
420101601870	VC-SCH-4.0-16t	16	42	27	60	30	29	27	96	91	2.78
420102501870	VC-SCH-5.0-25t	25	47	30	72	36	33	30	107	110	4.38
420103151870	VC-SCH-6.0-31-5t	31.5	53	34	78	39	37	34	121	120	5.91

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved