

Tensioner RUD ICE-CURT-K-GAKO

Product information




- Easy to handle (also with gloves)
- Innovative forged design – light and robust
- Patented, practical prevention of loosening
- Magnetically clinging locking device - also suitable as anti-theft system (lockable)
- Easy to clean and to grease

... [Read more](#)

Marking: According to standard
Temperature range: -60°C up to 200°C
Standard: EN 12195-3

Tensioner RUD ICE-CURT-K-GAKO

Blueprint



Technical data

| Part code | Code | LC daN | MBL ton | A mm | B mm | T mm | Weight kg |
|-----------------|--------------------|--------|---------|------|------|------|-----------|
| 705100370000570 | ICE CURT-K-6-GAKO | 3,600 | 3.67 | 400 | 140 | 260 | 1.76 |
| 705100610000570 | ICE CURT-K-8-GAKO | 6,000 | 6.11 | 520 | 170 | 350 | 3.15 |
| 705101020000570 | ICE CURT-K-10-GAKO | 10,000 | 10.19 | 532 | 170 | 362 | 3.55 |
| 705101630000570 | ICE CURT-K-13-GAKO | 16,000 | 16.31 | 300 | 830 | 530 | 6.57 |
| 705102550000570 | ICE CURT-K-16-GAKO | 25,000 | 25.49 | 962 | 350 | 612 | 12.22 |