Lifting Solutions Group
Axel Johnson International

# Master Link 4-legs RUD VIP

## Product information



VAK 4-leg master link with 4 all direction movable, welded VRG connectors. Thus ensuring that only the correct chain diameter and number of legs can be connected. VIP-Master link is marked by the RUD-ID-TAG® (RFID chip) and with the clear identification number distinguished. Complete identification tag with an integrated testing gauge. Pre-assembled connecting bolt and tensioning sleeve.

... *Read more*

**Marking:** According to standard
**Temperature range:** -60°C up to 200°C
**Standard:** EN 1677-4

**Safety factor:** 4:1
**Grade:** 10


**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

# Master Link 4-legs RUD VIP

## Blueprint




## Technical data

| Part code | Code | WLL ton | A mm | B mm | C mm | D mm | E mm | F mm | T mm | Weight kg |
|---|---|---|---|---|---|---|---|---|---|---|
| 42157984447 | VAK-3/4-4 | 1.32 | 10 | 35 | 60 | - | - | - | 106 | 0.34 |
| 42157100742 | VAK-4-6 | 3.15 | 18 | 75 | 135 | - | - | - | 217 | 1.8 |
| 42157100748 | VSAK-4-6 / 140 | 3.15 | 22 | 140 | 260 | - | - | - | 342 | 3.19 |
| 42157100751 | VSAK-4-6 / 190 | 3.15 | 22 | 190 | 350 | - | - | - | 432 | 3.83 |
| 42157100743 | VAK-4-8 | 5.25 | 22 | 90 | 160 | - | - | - | 268 | 3.4 |
| 42157100749 | VSAK-4-8 / 140 | 5.25 | 26 | 140 | 260 | - | - | - | 367 | 4.86 |
| 42157100752 | VSAK-4-8 / 190 | 5.25 | 26 | 190 | 350 | - | - | - | 457 | 5.9 |
| 42157100744 | VAK-4-10 | 8.4 | 26 | 100 | 180 | - | - | - | 311 | 5.5 |
| 42157100750 | VSAK-4-10 / 140 | 8.4 | 32 | 140 | 260 | - | - | - | 391 | 7.99 |
| 42157100753 | VSAK-4-10 / 190 | 8.4 | 32 | 190 | 350 | - | - | - | 481 | 9.34 |
| 42157100755 | VSAK-4-10 / 250 | 8.4 | 36 | 250 | 460 | - | - | - | 591 | 13.47 |
| 42157100745 | VAK-4-13 | 14.1 | 32 | 110 | 200 | - | - | - | 373 | 10.4 |
| 42157100754 | VSAK-4-13 / 190 | 14.1 | 36 | 190 | 350 | - | - | - | 523 | 14 |
| 42157100756 | VSAK-4-13 / 250 | 14.1 | 40 | 250 | 460 | - | - | - | 634 | 18.95 |
| 42157100746 | VAK-4-16 | 21.2 | 36 | 140 | 260 | - | - | - | 470 | 17.6 |
| 42157100757 | VSAK-4-16 / 250 | 21.2 | 51 | 250 | 460 | - | - | - | 671 | 32.42 |
| 42157104181 | VAK-4-20 | 33.6 | 51 | 190 | 350 | - | - | - | 614 | 39.1 |
| 42157993210 | VSAK-4-20 / 250 with VVS-20 | 33.6 | 54 | 250 | 460 | 36 | 75 | 170 | 754 | 48.36 |
| 42157100747 | VAK-4-22 | 42 | 51 | 190 | 350 | - | - | - | 644 | 45.7 |
| 42157993211 | VSAK-4-22 / 250 with VVS-22 | 42 | 57 | 250 | 460 | 40 | 80 | 170 | 763 | 56.7 |

**Certex Polska**
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved