



Master Link 4-legs RUD VIP

Product information

VAK 4-leg master link with 4 all direction movable, welded VRG connectors. Thus ensuring that only the correct chain diameter and number of legs can be connected. VIP-Master link is marked by the RUD-ID-TAG® (RFID chip) and with the clear identification number distinguished. Complete identification tag with an integrated testing gauge. Pre-assembled connecting bolt and tensioning sleeve.

Marking: According to standard

Temperature range: -60°C up to 200°C

Standard: EN 1677-4

Safety factor: 4:1

Grade: 10

Part code	Code	WLL ton	A mm	B mm	C mm	D, mm	E mm	F mm	T mm	Weight kg
42157984447	VAK-3/4-4	1.32	10	35	60	-	-	-	106	0.34
42157100742	VAK-4-6	3.15	18	75	135	-	-	-	217	1.8
42157100748	VSAK-4-6 / 140	3.15	22	140	260	-	-	-	342	3.19
42157100751	VSAK-4-6 / 190	3.15	22	190	350	-	-	-	432	3.83
42157100743	VAK-4-8	5.25	22	90	160	-	-	-	268	3.4
42157100749	VSAK-4-8 / 140	5.25	26	140	260	-	-	-	367	4.86
42157100752	VSAK-4-8 / 190	5.25	26	190	350	-	-	-	457	5.9
42157100744	VAK-4-10	8.4	26	100	180	-	-	-	311	5.5
42157100750	VSAK-4-10 / 140	8.4	32	140	260	-	-	-	391	7.99
42157100753	VSAK-4-10 / 190	8.4	32	190	350	-	-	-	481	9.34
42157100755	VSAK-4-10 / 250	8.4	36	250	460	-	-	-	591	13.47
42157100745	VAK-4-13	14.1	32	110	200	-	-	-	373	10.4
42157100754	VSAK-4-13 / 190	14.1	36	190	350	-	-	-	523	14
42157100756	VSAK-4-13 / 250	14.1	40	250	460	-	-	-	634	18.95
42157100746	VAK-4-16	21.2	36	140	260	-	-	-	470	17.6
42157100757	VSAK-4-16 / 250	21.2	51	250	460	-	-	-	671	32.42
42157104181	VAK-4-20	33.6	51	190	350	-	-	-	614	39.1
42157993210	VSAK-4-20 / 250 with VVS-20	33.6	54	250	460	36	75	170	754	48.36
42157100747	VAK-4-22	42	51	190	350	-	-	-	644	45.7
42157993211	VSAK-4-22 / 250 with VVS-22	42	57	250	460	40	80	170	763	56.7

Blueprint

