CERTEX | Lifting Solutions Group
Axel Johnson International

Boulder Grab

Product information



The boulder grab was developed for the simple transport of irregular stones and boulders. Of course, elements with parallel sides can also be transported.

The large lever transmission and the rotating clamping jaw guarantee a stable load handling. The roughly profiled clamping jaws ensure a safe gripping. The clamping jaws can be replaced by hardened tips.

The holding down device is adjustable in height. When handling assymmetrical loads with an eccentric center of gravity the suspension eye can be exactly positioned above the center of gravity. The clamping jaws can be adjusted on both sides via bolts.

The boulder grab can be used with any material handling lifting equipment near to the ground. Remove bolt when picking up the load. When setting down the load the bolt will snap in by itself and the grab opens automatically.

Features:

- Large clamping range
- Adjustable suspension eye
- Large rotating range
- Large gripping depth
- Low weight

Technical Specification:

- Clamping range: 0 - 920 mm
- Rotating range: on both sides approx. 15°
- Gripping depth: approx. 250 mm
- Total length: approx. 1.500 mm

... *Read more*

Note: Paint: orange, RAL 2000; beam and joining elements are galvanized

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Boulder Grab

Technical data

Part code	Code	WLL ton	Jaw width mm	Weight kg
502100109203050	STG 1-100	1	0-920	91
502100159203050	STG 1.5-100	1.5	0-920	96

Certex Polska
info@certex.pl
+48 91 817 28 49

© November 2026 - All Rights Reserved