



Alpha-Levator Vacuum Lifter

Product information

The ideal vacuum lifter – battery- or mains operated.

All smooth/rough and air-tight plates like tiles, natural stone- or concrete plates, plastics, metal plates or glass can be lifted easily: immediately after the Levator is positioned, it attaches itself securely to the plate and the load can be easily lifted and handled. The Levator releases the plate, when required: press the button and the valve opens. Wall tiles can also be rotated vertically.

Specification

The Alpha Levator consists of a strong aluminium plate with handle. A vacuum pump operated by battery or mains, creates the vacuum. The vacuum chamber at the bottom side is sealed by an elastic rubber. The self-adhesive sealing can easily be exchanged.

Basic equipment

Scope of delivery: vacuum lifter with a strong handle, vacuum pump, filter, valve and a robust plastic carrying case. The basic equipment can either be operated by battery or mains.

Battery kit

Lithium-ion batteries have no memory effect and allow permanent operation of approx 3 hours. Both batteries are equipped with integrated protective electronics. Charging time of the charger for 220 V - 50 Hz requires approx 2.5 hours.

Mains kit

The basic equipment is connected with the 220 V - 50 Hz mains by a 5 m cable and the power pack.

Features

- Ideal for tilers, landscape gardeners, glaziers or natural stone business
- High energy by lithium-ion batteries
- For smooth and rough surfaces
- Suited for almost all air-tight materials like tiles, natural stone-, concrete plates, plastics, glass, metal, etc.

Part code	WLL ton	Model	Dimensions mm	WLL Vertical ton	Weight kg
5605810050	0.05	Basic	120 x 260	0.015	1.5
5605810055	0.05	Basic S	80 x 350	0.015	1.5

